

Gallery of USAF Weapons

2009 USAF Almanac

By Susan H. H. Young

Note: Inventory numbers are total active inventory figures as of Sept. 30, 2008.

Bombers

B-1 Lancer

Brief: A long-range, air refuelable multirole bomber capable of flying intercontinental missions and penetrating enemy defenses with the largest payload of guided and unguided weapons in the Air Force inventory.

Function: Long-range conventional bomber.

Operator: ACC, AFMC.

First Flight: Dec. 23, 1974 (B-1A); Oct. 18, 1984 (B-1B).

Delivered: June 1985-May 1988.

IOC: Oct. 1, 1986, Dyess AFB, Tex. (B-1B).

Production: 104.

Inventory: 66.

Unit Location: Dyess AFB, Tex., Edwards AFB, Calif., Ellsworth AFB, S.D.

Contractor: Boeing; AIL Systems; General Electric.

Power Plant: four General Electric F101-GE-102 turbofans, each 30,780 lb thrust.

Accommodation: four, pilot, copilot, and two systems officers (offensive and defensive), on zero/zero ACES II ejection seats.

Dimensions: span spread 137 ft, swept aft 79 ft, length 146 ft, height 34 ft.

Weights: empty 192,000 lb, max operating weight 477,000 lb.

Ceiling: more than 30,000 ft.

Performance: max speed at low level high subsonic; 900+ mph (Mach 1.2 at S/L); range intercontinental.

Armament: three internal weapons bays capable of accommodating a wide range of weapons incl up to 84 Mk 82 (500-lb) or 24 Mk 84 (2,000-lb) general-purpose bombs; up to 84 Mk 62 (500-lb) or 8 Mk 65 (2,000-lb) Quick Strike naval mines; up to 30 cluster munitions (CBU-87/89/97) or 30 Wind-Corrected Munitions Dispensers (WCMD) (CBU 103/104/105); up to 24 GBU-31 (2,000-lb) or 15 GBU-38 (500-lb) Joint Direct Attack Munitions (JDAMs); up to 24 AGM-158A Joint Air-to-Surface Standoff Missiles (JASSMs); or any mix of these weapons (a different type of weapon in each of three weapons bays).

COMMENTARY

Of blended wing/body configuration, the B-1's variable-geometry design and turbofan engines combine to provide greater range, maneuverability, and high speed while enhancing survivability. Forward wing sweep settings are used primarily for takeoff, landings, air refueling, high-altitude cruise, and some weapons employment scenarios. The B-1 utilizes aft wing positions as its main combat configurations for high-subsonic and supersonic flight, enhancing maneuverability in the low- and high-altitude regimes. The B-1's speed and superior handling characteristics allow it to seamlessly integrate in mixed force packages. These capabilities, when combined with its substantial payload, excellent radar targeting system, long loiter time, and survivability, make the B-1 a key element of any joint/composite strike force.

The bomber's offensive avionics include high-resolution synthetic aperture radar (SAR), capable of tracking, targeting, and engaging moving vehicles, as well as self-targeting and terrain-following modes. In addition, an extremely accurate Global Positioning System-aided Inertial Navigation System (GPS/INS) enables aircrews to autonomously navigate globally, without the use of ground-based navigation aids and to engage targets with a high level of precision. The recent addition of Combat Track II (CT II) radios permit an interim secure beyond-line-of-sight (BLOS) reachback connectivity until Link 16 is integrated on the aircraft. In a time-sensitive targeting environment, the aircrew can receive targeting data from the combined air operations center over CT II, and then update mission



B-1 Lancer (Clive Bennett)

data in the offensive avionics system to strike emerging targets rapidly and efficiently.

The B-1's self-protection electronic jamming equipment, radar warning receiver (ALQ-161), and expendable countermeasures (chaff and flare) system complements its low radar cross section to form an integrated, robust onboard defense system that supports penetration of hostile airspace.

B-1A. USAF initially sought this new bomber as a replacement for the B-52, developing and testing four prototypes in the 1970s, but the program was canceled in 1977. Flight-test of the four B-1A models continued through 1981.

B-1B. The B-1B is an improved variant initiated in 1981. Major changes included the addition of additional structure to increase payload by 74,000 lb, an improved radar, and reduction of the radar cross section (RCS). The inlet was extensively modified as part of this RCS reduction, necessitating a reduction in maximum speed to Mach 1.2. The first production model flew in October 1984. USAF produced a total of 100 B models, but reduced the inventory to 67 aircraft with consolidation in 2002 at two main operating bases—Dyess AFB, Tex. and Ellsworth AFB, S.D.

The B-1B was first used in combat in support of operations against Iraq during Desert Fox in December 1998. In 1999, six B-1s were used in Allied Force, delivering more than 20 percent of the total ordnance while flying less than two percent of the combat sorties. The eight B-1s deployed in support of Enduring Freedom dropped nearly 40 percent of the total tonnage during the first six months of the operation. This included nearly 3,900 JDAMs, or 67 percent of the total.

The Conventional Mission Upgrade Program (CMUP) has significantly enhanced B-1B lethality and survivability. Block D upgrades included GPS receivers, a MIL-STD-1760 weapon interface, secure interoperable radios, and capability to employ precision weapons. Block E, which completed its final delivery in August 2006, included follow-on computer and software upgrades permitting simultaneous carriage of mixed guided and unguided weapons and WCMD, JASSM, and JSOW integration. Future upgrades will provide improved network-centric warfighting capability with cockpit avionics upgrades to enhance crew communications and situational awareness. A program to provide a fully integrated data link capability, including Link 16 and Joint Range Extension along with upgraded displays at the rear crew stations, began in FY05. In addition, a radar maintainability improvement

effort began in FY06, to be followed by integration of a targeting pod capability beginning in FY10. USAF began fielding the Sniper targeting pod in mid-2008 as an interim quick-reaction capability, using the rear station laptop computer for pod control.

As part of USAF's program to reduce fuel operating costs, the B-1B now is certified for unlimited use of synthetic fuel blend.

B-2 Spirit

Brief: Stealthy, long-range multirole bomber that can deliver nuclear and conventional munitions anywhere on the globe by flying through previously impenetrable defenses.

Function: Long-range heavy bomber.

Operator: ACC, ANG.

First Flight: July 17, 1989.

Delivered: Dec. 20, 1993-2002.

IOC: April 1997, Whiteman AFB, Mo.

Production: 21.

Inventory: 20.

Unit Location: Active and ANG (assoc.): Whiteman AFB, Mo.

Contractor: Northrop Grumman; Boeing; Vought.
Power Plant: four General Electric F118-GE-100 turbofans, each 17,300 lb thrust.

Accommodation: two, mission commander and pilot, on zero/zero ejection seats.

Dimensions: span 172 ft, length 69 ft, height 17 ft.
Weight: empty 125,000-153,700 lb, typical T-O weight 336,500 lb.

Ceiling: 50,000 ft.

Performance: minimum approach speed 140 mph, typical estimated unrefueled range for a hi-lo-hi mission with 16 B61 nuclear free-fall bombs is 5,000 miles, with one aerial refueling more than 10,000 miles.

Armament: in a nuclear role: up to 16 nuclear weapons (B61 Mod 7, B61 Mod 11, B83) on rotary launchers. In a conventional role, 80 Mk 82 500-lb bombs, 34 tactical munitions dispensers, 80 Mk 62 sea mines, or 80 GBU-38 (500-lb) JDAMs mounted on bomb rack assemblies, or up to 16 rotary launcher-mounted weapons: 16 GBU-31 (2,000-lb) JDAMs, or a penetration version of a BLU-109, or 16 Mk 84 2,000-lb bombs; 16 Joint Standoff Weapons (JSOWs), 16 JASSMs, or eight 4,700-lb GBU-37/GBU-28C/B guided weapons. Future weapons include Small Diameter Bomb (SDB) II.



B-2A Spirit (MSGt. Kevin J. Gruenwald)

COMMENTARY

The B-2 bomber is a unique, highly advanced system, combining sophisticated technologies, notably low observable (LO) stealth design, with high aerodynamic efficiency, enabling it to attack heavily defended targets and neutralize enemy defenses.

Based on the flying wing concept, the B-2 has no vertical tail surfaces. The smoothly blended "fuselage" section accommodates two flight crew and two large weapons bays side by side in the lower centerbody. These bays contain rotary launchers or bomb rack assemblies capable of carrying up to 40,000 lb of weapons.

Four nonafterburning turbofan engines are mounted in pairs within the wing structure, with scalloped over-wing intake ducts and shielded over-wing trailing edge nozzles. The aircraft has a quadruple-redundant fly-by-wire digital flight-control system, actuating moving surfaces at the wing trailing edges that combine aileron, elevator, and rudder functions. A landing gear track of 40 ft enables the B-2 to use any runway that can handle a Boeing 727 airliner.

B-2A. B-2 production represents three successive blocks of capability. Block 10 aircraft carried B83 nuclear bombs or 16 Mk 84 2,000-lb conventional munitions. Block 20 aircraft additionally carried B61/7 and B61/11 nuclear bombs, as well as GPS-aided munitions (GAMs), and GBU-36B, on two rotary launcher assemblies, providing an interim, near-precision strike capability. All Block 10 and 20 aircraft are upgraded to Block 30. (The last original Block 20 B-2, used as a test aircraft at Edwards AFB, Calif., was refurbished as an operational bomber and entered operational service in September 2002.)

Block 30 configuration added significant new weapons capability. Using the rotary launcher assembly, all B-2s are capable of employing 16 Mk 84 JDAMs, 16 JSOWs, 16 JASSMs, 16 BLU-109 JDAMs, or eight GBU-37s or GBU-28C/Bs. All B-2s are also capable of substituting bomb rack assemblies in place of the rotary launchers, providing the capability to employ 80 500-lb Mk 82s. Modifications to the bomb racks add carriage of 80 independently targeted GBU-38 (500-lb) JDAMs. Other Block 30 enhancements include fully operational defensive and offensive avionics, a more sophisticated mission planning system, and additional operating modes for the synthetic aperture radar. A new stealth coating introduced under the Alternative High Frequency Material (AHFM) program is dramatically improving combat readiness. The entire fleet will be converted by 2012. Additionally, Link 16 digital data sharing capability and the replacement of the current mechanically scanned phased-array antenna with an active electronically scanned array (AESA) radar are ongoing.

Beyond Block 30, USAF plans to add UHF/EHF satellite communications systems.

The first use of B-2s in combat took place March 24, 1999, against Serb targets in Allied Force, with two aircraft each dropping 16 JDAMs. In October 2001, B-2s flew the longest combat sorties during Enduring Freedom, flying 44-hour sorties from Whiteman AFB, Mo., striking targets in Afghanistan, then landing in Diego Garcia for an engine running crew change, with the second crew flying a 29-hour sortie back to Whiteman. B-2s operate from three forward locations—Andersen AFB, Guam, RAF Fairford, UK, and Diego Garcia in the Indian Ocean.

B-52 Stratofortress

Brief: A long-range, heavy multirole bomber that can carry nuclear or conventional ordnance or cruise missiles, with worldwide precision navigation capability.

Function: Long-range heavy bomber.

Operator: ACC, AFMC, AFRC.

First Flight: April 15, 1952 (YB-52 prototype).

Delivered: November 1955-October 1962.



B-52H Stratofortress (Clive Bennett)

IOC: June 19, 1955.

Production: 744.

Inventory: 76.

Unit Location: Active: Barksdale AFB, La., Edwards AFB, Calif. (AFMC), Minot AFB, N.D. AFRC: Barksdale AFB, La.

Contractor: Boeing.

Power Plant: eight Pratt & Whitney TF33-P-3 turbofans, each 17,000 lb thrust.

Accommodation: two pilots, side by side, plus navigator, radar navigator, and electronic warfare officer.

Dimensions: span 185 ft, length 159.3 ft, height 40.7 ft.

Weight: empty approx 188,000 lb, gross 488,000 lb.

Ceiling: 50,000 ft.

Performance (approx): max level speed 449 mph, range more than 10,000 miles.

Armament: 12 AGM-86B Air Launched Cruise Missiles (ALCMs) externally, with provision for eight more ALCMs or gravity weapons internally. Conventional weapons incl AGM-86C/D Conventional ALCMs (CALCMs), naval mines, bombs up to 2,000 lb, CBU 87/89/97 unguided munitions, CBU-103/104/105 Wind-Corrected Munitions Dispenser (WCMD) guided munitions, GBU-31 and GBU-38 JDAMs, JASSMs, and GBU-10/12/28 laser guided bombs. Future weapons incl the Miniature Air Launched Decoy (MALD).

COMMENTARY

The B-52's still-expanding weapons capability reflects its continued ability to perform a wide range of missions, including show of force, maritime operations, long-range precision strikes, close air support (CAS), offensive counter-air, air interdiction, and defense suppression. USAF still is reviewing a standoff electronic warfare role for the B-52.

Equipment includes GPS, ARC-210 radios with Have Quick II anti-jam feature, KY-100, providing secure voice and data transmission, an electro-optical (EO) viewing system that uses forward-looking infrared (FLIR) and high-resolution low-light-level television (LLTV) sensors to augment the targeting, battle assessment, flight safety, and terrain-avoidance systems, improving combat and low-level flight capability, and night vision goggles (NVGs). B-52s are modified to carry weapons targeting pods. Future plans include modification of the entire fleet with an integrated self-targeting and battle damage assessment (BDA) capability and a new radar system. A MIL-STD-1760 interface supports advanced precision weapons capability. The B-52's ECM suite uses a combination of electronic detection, jamming, and infrared (IR) countermeasures to protect against hostile air defense systems.

The B-52 was the first USAF aircraft to fly using synthetic fuel. It also was first to release the massive ordnance penetrator (MOP) weapon.

Several versions of the Stratofortress were produced, including:

B-52A. Initial production version, with J57-P-1W engines and provision for in-flight refueling. First flown Aug. 5, 1954, the three aircraft built were used by Boeing for technical development purposes. Delivered to SAC November 1957. Finally retired 1969.

B-52B. First operational version, 23 of which were built. Also, 27 RB-52B dual-role bomber/reconnaissance variants. First flown January 1955, with deliveries between June 1955-August 1956; powered by J57-P-1W, -19W, -29W, or -29WA engines. Retired in the mid-1960s.

B-52C. Multimission version with increased gross weight and larger under-wing tanks. Powered by J57-P-19W or -29WA engines. First flown March 1956; 35 were delivered June-December 1956. Majority retired 1971.

B-52D. Long-range bomber version, first flown June 1956 and used during the Vietnam War. Total of 170 built, with deliveries beginning late 1956. Retired 1982-83.

B-52E. Version with improved bombing, navigation, and

electronics systems. First flown October 1957. One hundred delivered October 1957-June 1958. Retired 1969-70.

B-52F. Version with updated J57-P-43WA engines, first flown in May 1958. Eighty-nine delivered June 1958-February 1959. Retired 1978.

B-52G. Introduced important design changes, including a redesigned wing containing integral fuel tanks for increased range, fixed under-wing external tanks, a shorter tail fin of greater chord, and a remotely controlled tail gun turret that allowed the gunner to be repositioned with the rest of the crew. Initial flight August 1958, with the first of 193 aircraft entering service in February 1959. Operated as the primary bomber during the first Gulf War. Retired 1994.

B-52H. The only version still in service, the H introduced TF33 turbofans, providing increased unrefueled range, and improved defensive armament. First flown July 1960, 102 were built, with deliveries between May 1961 and October 1962. The B-52 currently is employable for both conventional and nuclear missions. As the Air Force's only nuclear cruise missile carrier, it performs multiple cruise missile launches at high altitude, often followed by B-52 penetration to attack other targets. When tasked with precision weapons delivery, it conducts close air support and attacks targets using GPS/INS guided air support.

Ongoing modernization of its conventional capabilities is extending the B-52's service life well into the 21st century, with the ability to provide massive firepower in low- to midthreat environments supplemented by a standoff attack capability. Iraqi Freedom saw B-52s delivering laser guided bombs for the first time using Litening targeting pods. Use of heavy stores adapter beams enable aircraft to carry most B-52-certified munitions. ALCMs and CALCMs are carried on unique pylons or internally on a rotary launcher. Avionics improvements include the Avionics Midlife Improvement (AMI) Program, which replaces the current system processors, inertial navigation unit (INU), and data transfer system (DTS) cartridges. Electronic attack improvements include the ECM improvement upgrade to the ALQ-172 set. The Combat Network Communications Technology (CONNECT) improvement provides a modern cockpit information avionics architecture, color displays, and enhanced situational awareness, network-centric warfighting capability, fully integrated line-of-sight (LOS) and beyond-line-of-sight (BLOS) data link capabilities, and mission/weapon reprogramming capability. The B-52 EHF program will add UHF/EHF satellite communications to the fleet.

Fighter and Attack Aircraft

A-10 Thunderbolt II

Brief: A simple, effective, twin-engine aircraft specifically designed for close air support (CAS) of ground forces against a wide range of ground targets, including tanks and other armored vehicles.

Function: Attack aircraft.

Operator: ACC, AFMC, PACAF, USAF, ANG, AFRC.

First Flight: Feb. 15, 1975 (preproduction).

Delivered: November 1975-March 1984.

IOC: October 1977.

Production: 713.

Inventory: 335 (A-10A); 128 (A-10C).

Unit Location: Active: Davis-Monthan AFB, Ariz., Eglin AFB, Fla., Moody AFB, Ga., Nellis AFB, Nev., Osan AB, South Korea, Spangdahlem AB, Germany. ANG: Boise Air Terminal, Idaho, Fort Smith Arpt., Ark., Martin State Arpt., Md., Selfridge ANGB, Mich. AFRC: Barksdale AFB, La., Langley AFB, Va., Whiteman AFB, Mo.

Contractor: Fairchild Republic; now Lockheed Martin.

Power Plant: two General Electric TF34-GE-100 turbofans, each 9,065 lb thrust.

Accommodation: pilot only, on zero-height/518 mph-zero-speed ejection seat.

Dimensions: span 57.5 ft, length 53.3 ft, height 14.7 ft.

Weight: empty 28,000 lb, max gross 51,000 lb.

Ceiling: 37,000 ft.

Performance: speed 518 mph, combat range with 9,500 lb of weapons and 1.7 hr loiter, 20 min reserve, 288 miles.

Armament: one 30 mm, seven-barrel, 1,174-rd capacity GAU-8 Gatling gun capable of carrying inert target practice (TP) rds, straight high-explosive incendiary (HEI), or anti-armor tailored HEI/API "combat mix"; 11 hardpoints for up to 16,000 lb of ordnance, incl various types of free-fall or guided bombs, such as Mk 82, Mk 84, GBU-10/12/16/38, CBU-87 Combined Effects Munition (CEM), WCMD, 2.75-in high-explosive, white phosphorous, and overt/covert illumination rockets, SUU-25 overt/covert flare dispensers, up to six AGM-65B/D/E/G/H/K Maverick missiles, and up to four AIM-9 Sidewinder missiles. Up to 480 chaff and flares carried internally to counter radar or IR threats. Up to three 600-gallon fuel tanks can also be carried.

COMMENTARY

Supporting the CAS, airborne forward air controller (FAC(A)), interdiction, combat search and rescue (CSAR) ("Sandy") missions, and special operations forces (SOF) support, the A-10 combines large diverse weapons payload, long loiter, austere airfield capability, maneuverability, and wide combat radius with the ability to operate under 1,000-ft ceilings, with 1.5-mile visibility, or up to 25,000 ft with advanced targeting pods and GPS-guided munitions or in darkness with NVGs. In a typical mission, the A-10, nicknamed Warthog, can fly 150 miles with a standard payload and remain on station (loiter) for two hours or much longer with air refueling. The 30 mm GAU-8 gun provides a cost-effective weapon with which to defeat a wide array of ground targets, including heavily armored tanks. The gun-rocket-Maverick medley provides a unique combination of "point-shoot," low-collateral damage, and mobile target capabilities demanded by the danger-close proximity to friendly forces or urban terrain. The cockpit is protected with titanium armor, capable of withstanding projectiles up to 23 mm. A-10s were used extensively in Desert Storm, Allied Force, and in Southwest Asia operations, where they have conducted several A-10 combat firsts, including first use of Litening II targeting pod, first self-lased laser guided bomb (LGB) delivery, and first AGM-65E/H/K and JDAM employment. The A-10 is projected to serve well into the 2020s.

A-10A equipment includes an enhanced GPS/INS (EGI), head-up display (HUD), NVGs, and an Integrated Flight and Fire Control Computer (IFFCC) to enhance weapons delivery accuracy, cockpit presentations, targeting pod integration, and terrain avoidance. Other equipment consists of Pavé Penny laser target identification pod and self-protection/penetration aids, including ALQ 131/184 ECM pods, ALR-69 radar warning receiver (RWR), AAR-47 missile warning system, and countermeasures system (CMS) to digitally integrate the ALE-40 chaff-flare dispenser and automate future extended IRCM solutions.

A-10C is the new designation for aircraft currently being upgraded with the precision engagement modification, with new multifunction color displays, hands-on throttle and stick (HOTAS), digital stores management, JDAM/WCMD integration, Sniper targeting pod capability, a Situational Awareness Data Link (SADL), and integration of sensors with aircraft systems. IOC occurred in August 2007, with the first combat deployment one month later. All aircraft are scheduled to be modified by FY11. Other planned improvements include enhanced communication and improved situational awareness systems. These improvements will



A-10 Thunderbolt II (MSgt. Andy Dunaway)

permit the A-10 to attack from higher altitudes and provide a better logistical and maintenance footprint. Additionally, the entire fleet is to receive structural improvements including rewinging where necessary.

Aircraft designated **OA-10A/C** are used primarily for FAC(A), combat escort, CSAR, and visual reconnaissance missions. The OA-10 is identical to the A-10. Mission configurations typically include large weapons loads of white phosphorous marking rockets and covert/overt illumination rockets/flares to mark/illuminate targets for strike aircraft or friendly ground forces. The first OA-10 unit reached initial operational capability (IOC) in October 1987.

AC-130 Gunship

Brief: Heavily armed aircraft using side-firing weapons integrated with sophisticated sensor, navigation, and fire-control systems to provide precise firepower or area saturation for long periods, at night and in adverse weather.

Function: Attack aircraft.

Operator: AFSOC.

First Flight: 1967.

Delivered: 1968-present.

IOC: 1972 (AC-130H); 1996 (AC-130U).

Production: 43; incl four recent conversions.

Inventory: eight (AC-130H); 17 (AC-130U).

Unit Location: Cannon AFB, N.M. (scheduled), Hurlburt Field, Fla.

Contractor: Lockheed Martin (airframe); Boeing (AC-130H); Rockwell, now Boeing (AC-130U).

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: crew of 13.

Dimensions: span 132.6 ft, length 99 ft, height 38.5 ft.

Weight: gross 155,000 lb.

Ceiling: 25,000 ft.

Performance: speed 289 mph, range 1,500 miles, with air refueling unlimited.

Armament: two 20 mm Vulcan cannons with 3,000 rd (AC-130H); one 25 mm Gatling gun (AC-130U); one 40 mm Bofors cannon with 256 rd, and one 105 mm Howitzer with 100 rd.

COMMENTARY

The AC-130 is a C-130 modified with gun systems, electronic and EO sensors, fire-control systems, enhanced navigation systems, sophisticated communications, defensive systems, and in-flight refueling capability. These

systems give the gunship crew the capability to acquire and identify targets day or night, coordinate with ground forces and command and control (C2) agencies, and deliver surgical firepower in support of both conventional and special operations missions. For operations in Afghanistan and Iraq, the AC-130 gunships work in conjunction with the MQ-1 Predator, the latter providing live video and target referencing information.

AC-130A was the initial version, deployed in Vietnam 1968-69. Eighteen produced.

AC-130E, an improved version, of which eight were built. Converted to H standard after service in Vietnam.

AC-130H Spectre aircraft are scheduled to serve with the 27th SOW at Cannon AFB, N.M. AC-130Hs are equipped with a digital fire-control computer, EO sensors, and target-acquisition systems, including FLIR and LLLTV, and are capable of in-flight refueling. Fire-control computers, navigation, communications, and sensor suites have been upgraded. Future modifications include a new ground mapping/weather radar, enhanced traffic alert and collision avoidance system (ETCAS), large aircraft infrared countermeasures (LAIRCM), and expanded precision weapons capability.

AC-130U Spooky aircraft serve with 1st SOW and are gunship conversions by Rockwell, of which 13 were delivered to AFSOC's 4th SOS in 1994-95. Four additional aircraft were recently converted by Boeing to U standard. A planned replacement to the 40 mm gun has been canceled. All weapons can be subordinated to the APQ-180 digital fire-control radar, FLIR, or all-light-level television (ALLTV) for adverse weather attack operations. Future modifications include ETCAS, Link 16, an advanced gunship multispectral sensor, and expanded precision weapons capability.

Although the AC-130H Spectre and AC-130U Spooky gunships use dissimilar avionics and other systems, fire support to troops on the ground is generally comparable. The primary mission for the gunship is close air support for special operations forces. Other missions include armed reconnaissance, interdiction, point defense, armed escort, and surveillance.

F-15 Eagle

Brief: A supersonic, all-weather, highly maneuverable tactical fighter designed to permit USAF to swiftly gain and maintain air superiority in aerial combat.



AC-130 Gunship (Rick Llinares)

Function: Air superiority fighter.

Operator: ACC, AETC, AFMC, PACAF, USAFE, ANG, AFRC.

First Flight: July 27, 1972.

Delivered: November 1974-85.

IOC: September 1975.

Production: 874.

Inventory: 407.

Unit Location: Active: Eglin AFB, Fla., Elmendorf AFB, Alaska, Kadena AB, Japan, Langley AFB, Va., Mountain Home AFB, Idaho, Nellis AFB, Nev., RAF Lakenheath, UK, Robins AFB, Ga., Tyndall AFB, Fla. ANG: Barnes Arpt., Mass., Great Falls Arpt., Mont., Hickam AFB, Hawaii, Jacksonville Arpt., Fla., Klamath Falls Arpt., Ore., NAS JRB New Orleans, La., Portland Arpt., Ore. AFRC: Langley AFB, Va. (assoc.), Nellis AFB, Nev.

Contractor: McDonnell Douglas (now Boeing); Raytheon.

Power Plant: F-15C: two Pratt & Whitney F100-PW-220 turbofans, each 25,000 lb thrust, with max afterburner.

Accommodation: pilot only in F-15A/C; two seats in F-15B/D.

Dimensions: span 42.8 ft, length 63.8 ft, height 18.7 ft.

Weight: empty 28,600 lb, gross 68,000 lb.

Ceiling: 65,000 ft.

Performance: F-15C: max speed Mach 2.5, T-O run 900 ft, landing run without braking parachute 3,500 ft, ferry range with external fuel tanks more than 2,878 miles.

Armament: one internally mounted M61A1 20 mm six-barrel cannon; up to four AIM-9L/M/X Sidewinder and up to four AIM-120 Advanced Medium-Range Air-to-Air Missiles (AMRAAMs), carried externally.

COMMENTARY

For more than 30 years, the F-15 has provided the capability to penetrate hostile defenses and establish air superiority over enemy systems through a combination of superior maneuverability and acceleration, range, weapons, and avionics. F-15 fighters deployed to Desert Storm accounted for 34 of the 37 USAF air-to-air victories, and in Iraqi Freedom F-15Cs led coalition aircraft in maintaining aerial dominance.

F-15A (single-seat) and **F-15B** (two-seat) fighters became USAF's front-line fighter immediately upon introduction in the mid-1970s. A multimission avionics system includes APG-63 pulse-Doppler radar for long-range detection and tracking of small high-speed objects down to treetop level and effective weapons delivery, a HUD for close-in combat, identification, friend or foe (IFF), and INS. F-15A/Bs now serve with ANG. F-15A/Bs retrofitted with E-kit upgrades have additional thrust and improved combat capability.

F-15C (single-seat) and **F-15D** (two-seat) models followed in June 1979. Improvements included 2,000 lb of additional internal fuel and provision for carrying conformal fuel tanks (CFTs), reducing in-flight refueling requirements and increasing time in the combat zone. From 1983 through 1997, tactical capabilities were enhanced extensively through the Multistaged Improvement Program (MSIP), a program of installation of new or modification of existing avionics equipment, allowing for the carriage of more advanced weapons, and increased self-protection. The last 43 aircraft were delivered with the APG-70 radar. The F-15C/Ds that USAF expects to remain in the fleet until 2025 have been further upgraded with the APG-63(V)1. One squadron in Alaska received the later APG-63(V)2, featuring an active electronically scanned array (AESA), permitting the aircraft to track multiple targets and to guide air-to-air missiles against them. The Joint Helmet Mounted Cueing System (JHMCS) is intended, along with the AIM-9X, to significantly enhance lethality in close-range aerial combat. Other modifications include improved

engines, GPS equipment, Litening targeting pods, and the Link 16 fighter data link; a proportion will receive the next generation APG-63(V)3 AESA radar.

All but nine F-15A-D models have been cleared to fly following a period of grounding for structural evaluation; five C models are being repaired and four retired.

F-15E Strike Eagle

Brief: A heavily modified, two-seat, dual-role variant of the original F-15, with weapons systems totally integrated for all-weather deep interdiction missions as well as air-to-air combat.

Function: Dual-role fighter.

Operator: ACC, AFMC, PACAF, USAFE.

First Flight: Dec. 11, 1986.

Delivered: April 1988-2004.

IOC: May 1989.

Production: 236.

Inventory: 223.

Unit Location: Eglin AFB, Fla., Mountain Home AFB, Idaho, Nellis AFB, Nev., RAF Lakenheath, UK, Robins AFB, Ga., Seymour Johnson AFB, N.C.

Contractor: McDonnell Douglas (now Boeing); Raytheon.

Power Plant: two Pratt & Whitney F100-PW-220, each

gross weight at takeoff and maneuver at nine Gs throughout the flight envelope. Cockpit controls and displays are improved, and a wide-field-of-view (WFOV) HUD is included.

For low-altitude, high-speed penetration and precision attack on tactical targets at night and in adverse weather, the F-15E carries a high-resolution APG-70 radar which provides a high-resolution synthetic aperture radar (SAR) map and LANTIRN (Low-Altitude Navigation and Targeting Infrared for Night) pods, with wide-field FLIR. The APG-70 gives the F-15E, with its AMRAAM and AIM-9 load, a true multirole capability. The triple-redundant digital flight-control system, in combination with the LANTIRN navigation pod and the WFOV HUD, permits automatic terrain following. Other improvements include an EGI and Link 16 data link. F-15E aircraft have been JDAM- and WCMD-capable since 2003. In addition, some F-15E aircraft have been equipped with Litening and Sniper targeting pods for improved precision attack capability. External CFTs have been fitted to increase combat range while carrying ordnance. System upgrades under way include programmable armament control sets (PACS), ready-installed software for delivery of JDAM and WCMD, and an enhanced night vision capability. New core processors ensuring increased capability and reliability are being retrofitted to allow employment of the



F-15E Strike Eagle (SSgt. Samuel Morse)

25,000 lb thrust; or F100-PW-229 turbofans, each 29,000 lb thrust with max afterburner.

Accommodation: crew of two, on zero/zero ejection seats.

Dimensions: span 42.8 ft, length 63.8 ft, height 18.5 ft.

Weight: empty 45,000 lb, gross 81,000 lb.

Ceiling: 50,000 ft.

Performance: max level speed at altitude Mach 2.5, ferry range with CFTs 3,000 miles.

Armament: one internally mounted M61A1 20 mm six-barrel cannon; up to four AIM-9 Sidewinder and up to four AIM-120 AMRAAMs or up to eight AIM-120 AMRAAMs; up to six AGM-65 Maverick air-to-surface missiles; AGM-130; EGBU-15 and GBU 10/12/15/24/28/31/38/54 guided munitions; CBU 87/89/97 unguided munitions; CBU-103/104/105 WCMD guided munitions, GBU-39 SDB, and nuclear weapons.

COMMENTARY

F-15E aircraft have a strengthened airframe for increased

GBU-39 SDB. A new AESA radar to replace the APG-70 is currently under development, aimed at improving targeting and mapping capabilities.

During Desert Storm, 48 USAF F-15Es were deployed to the Persian Gulf where they operated mainly at night, hunting Scud missile launchers and artillery sites using the LANTIRN system. The Strike Eagle can operate in conjunction with E-8 Joint STARS ground surveillance aircraft and has taken on a CAS role for Afghanistan operations.

F-16 Fighting Falcon

Brief: A compact, versatile, and low-cost multirole fighter aircraft that is highly maneuverable and has repeatedly proved itself in air-to-air combat, suppression of enemy air defenses (SEAD), and air-to-surface attack.

Function: Multirole fighter.

Operator: ACC, AETC, AFMC, PACAF, USAFE, ANG, AFRC.

First Flight: Dec. 8, 1976 (full-scale development).

Delivered: August 1978-2005.

IOC: October 1980, Hill AFB, Utah.

Production: 2,206.

Inventory: 1,200.

Unit Location: 9 active wings, 18 ANG, and three AFRC units (plus one associate).

Contractor: Lockheed Martin; Northrop Grumman.

Power Plant: one augmented turbofan. General Electric F110-GE-100 (27,600 lb thrust) and Pratt & Whitney F100-PW-220 (23,450 lb thrust) are alternative standard engines. Increased performance engines (IPEs) in aircraft delivered from late 1991: Block 50: F110-GE-129 (29,000 lb thrust); Block 52: F100-PW-229 (29,100 lb thrust).

Accommodation: pilot only, on zero/zero ejection seat.

Dimensions: wingspan with missiles 32.7 ft, length overall 49.4 ft, height 16.7 ft.

Weight: (F-16C) empty (F100-PW-229) 18,591 lb, (F110-GE-129) 18,917 lb; gross, with external load (Block 40/42) 42,000 lb.

Ceiling: 50,000 ft.

Performance: max speed Mach 2, radius of action: Block 40 with two 2,000-lb bombs, two AIM-9 missiles, and external fuel, hi-lo-lo-hi 852 miles; combat range 575 miles.

Armament: one M61A1 20 mm multibarrel cannon, with 511 rd, mounted in fuselage; wingtip-mounted missiles; seven other external stores stations for fuel tanks and a range of air-to-air and air-to-surface munitions.



F-16 Fighting Falcon (TSgt. Erik Gudmundson)



F-22A Raptor (MSgt. Andy Dunaway)

COMMENTARY

The F-16 is the workhorse of the USAF fighter fleet, supporting the majority of precision guided munitions taskings in combat operations. The 200+ USAF F-16 multimission fighters deployed to the Persian Gulf Theater flew more sorties than any other type during Desert Storm, with 13,500 missions. In the initial stages of Iraqi Freedom, the F-16 flew hundreds of missions helping to destroy the unit cohesion of the Republican Guard. F-16s continue to support operations in Iraq and Afghanistan while providing the majority of homeland defense forces for air sovereignty.

F-16A (single-seat) and **F-16B** (two-seat) versions incorporated advanced technologies from the start, making these aircraft two of the most maneuverable fighters built. USAF has retired almost all its A and B models, but the versions are still in use with many international operators. Equipment included a multimode radar with a clutter-free look-down capability, advanced radar warning receiver (RWR), HUD, internal chaff/flare dispensers, and a 500-rd 20 mm internal gun.

Production of the F-16A and B for USAF ended in 1985. A midlife update program, undertaken cooperatively by USAF and NATO operators, improved the radar, fire-control computer, stores-management computer, and avionics software, giving F-16A/Bs the ability to use next generation air-to-air and air-to-surface weapons. The Multinational Staged Improvement Program, implemented in 1980, ensured the aircraft could accept systems under development, thereby minimizing retrofit costs. All F-16s delivered since November 1981 featured built-in structural and wiring provisions and systems architecture that expanded the single-seater's multirole flexibility to perform precision strike, night attack, and beyond-visual-range intercept missions.

F-16C (single-seat) and **F-16D** (two-seat) aircraft were introduced at production Block 25 with MSIP II improvements in the cockpit, airframe, and core avionics and an increased-range APG-68 radar. Block 30 and 40 aircraft incorporate the General Electric F110-GE-100 engine. Deliveries began in 1984. With the exception of AFMC, all of the active, Guard, and Reserve units have since converted to F-16C/Ds. Block 40/50 aircraft are now GBU-31/38/54 JDAM, WCMD, and AGM-158 JASSM capable.

ANG and AFRC Block 25/30/32 F-16s have upgrades that increase throughput and memory for new weapon capabilities, including GBU-31/38/54 JDAM, plus advanced identification, friend or foe (AIFF) to reduce the risk of fratricide. These aircraft also carry the Theater Airborne Reconnaissance System (TARS), a podded system with EO sensors and future high-capacity data link to move the imagery to users on the ground.

ANG F-16s are equipped with Litening II/Litening ER and Sniper targeting pods. A structural modification program to remedy fatigue problems caused by increased usage rates and heavier than forecast gross weights has been undertaken under the Falcon STAR program.

F-16CG Block 40/42 aircraft specialize in night attack operations with precision guided weapons. Follow-on improvements include ALE-47 improved defensive countermeasures, ALR-56M advanced Very High Speed Integrated Circuit (VHSIC) technology in the APG-68(V5) fire-control radar, a ring-laser gyro INS, GPS, core avionics hardware, enhanced-envelope gunsight, digital flight controls, automatic terrain following, increased takeoff weight and maneuvering limits, an 8,000-hour airframe, IPEs, and expanded envelope nine-G capability.

F-16CJ designated Block 50/52 aircraft are equipped with the High-speed Anti-Radiation Missile (HARM) targeting system (HTS) for suppression of enemy air defenses (SEAD). Block 50/52 F-16CJs have MSIP Stage III improvements, which also show up in selected retrofits of earlier F-16 blocks. These aircraft incorporate the General Electric F110 and Pratt & Whitney F100 increased performance engines, the latest cockpit control and display technology, including a wide-angle HUD. Weapons improvements include multishot AMRAAM compatibility, GBU-31/38/54 JDAM, WCMD, AGM-158 JASSM, and laser guided bomb variants (GBU-10/12/24) using Sniper, Litening AT/R, and LANTIRN targeting pods. Downlink capability integrates with ROVER systems to support joint terminal attack controllers (JTAC) on the ground to increase close air support (CAS) effectiveness.

Block 50/52 aircraft, followed by Block 40/42 from 2006-10, have been undergoing a program of retrofit with a new modular mission computer developed under an F-16 Common Configuration Implementation Program (CCIP), aimed at extending operational flexibility and maintenance commonality. The CCIP software effort includes the participating European governments of the F-16 Multinational Fighter Program. CCIP hardware includes new color displays, Sniper XR targeting pod, JHMCS, AIM-9X, Link 16, and improved weapons capabilities. First delivery was made January 2002, and modification of Block 50/52 aircraft was completed in 2006; the Block 40/42 retrofit program is expected to finish by 2010. The Block 50/52 aircraft have dual/alternate carriage of HARM targeting system (HTS) and Smart Targeting and Identification via Networked Geolocation (STING) and advanced targeting pods (ATP). Planned future upgrades include enhanced GPS/INS, Miniature Air Launched Decoy (MALD) with new mission planning software and SDB integration.

F-22A Raptor

Brief: A fifth generation, multirole fighter designed to penetrate advanced anti-air threats and achieve air dominance.

Function: Air dominance multirole fighter.

Operator: ACC, AETC, AFMC, PACAF, ANG, AFRC.

First Flight: Sept. 7, 1997.

Delivery: 2002 (first production representative aircraft).

IOC: Dec. 15, 2005.

Production: 187 (planned).

Inventory: 121.

Unit Location: Edwards AFB, Calif., Elmendorf AFB, Alaska, Hickam AFB, Hawaii (active associate planned), Holloman AFB, N.M., Langley AFB, Va. (first operational location), Nellis AFB, Nev., Tyndall AFB, Fla. ANG: Hickam AFB, Hawaii (planned), Langley AFB, Va. (assoc.). AFRC: Elmendorf AFB, Alaska (assoc.), Holloman AFB, N.M. (assoc.).

Contractor: Lockheed Martin; Boeing.

Power Plant: two Pratt & Whitney F119-PW-100 turbofans, each in 35,000-lb thrust class.

Accommodation: pilot only, on zero/zero ejection seat.

Dimensions: span 44.5 ft, length 62 ft, height 16.6 ft.

Weight: gross 50,000 lb.

Ceiling: above 50,000 ft.

Performance (design target): max level speed at S/L 900+ mph, range more than 2,000 miles.

Armament: one internal M61A2 20 mm gun, two AIM-9 Sidewinders stored internally in the side weapons bays; six AIM-120 AMRAAMs or two AIM-120 AMRAAMs and two GBU-32 JDAMs for ground attack, stored internally in the main weapons bay; beginning 2011, up to eight SDBs can replace two JDAMs.

COMMENTARY

Built to lead USAF's "kick down the door" force, by day and night and in adverse weather and across the spectrum of missions, the **F-22A** represents an unparalleled combination of stealth, supercruise (ability to cruise at supersonic speed without using its afterburners), maneuverability, and integrated avionics allowing it to counter multiple anti-access threats. Integrated avionics and intraflight data link permit simultaneous engagement of multiple targets. The combination of flight controls, structural strength, and high-performance engines with thrust vectoring nozzles results in exceptional maneuverability. The cockpit is fitted with six color LCDs. The Primary Multifunction Display provides a view of the air and ground tactical situation, including threat identity, threat priority, and tracking information, with two Secondary Multifunction Displays showing air and ground threats, stores management, and air threat information. Two additional displays give navigation, communication, identification, and flight information. A HUD displays target status, weapon status, weapon envelopes, and shoot cues. Other equipment includes AN/APG-77 radar, an electronic warfare system with radar warning receiver and missile launch detector, JTIDS, IFF, laser gyroscope inertial reference, and GPS.

The F-22A entered engineering and manufacturing development (EMD) in August 1991. Initial operational test and evaluation (IOT&E) examining the Raptor's air dominance mission concluded mid-September 2004. JDAM capability was demonstrated that same month. Follow-on OT&E (FOT&E) completed in 2005. The F-22A had proved its air-to-air and air-to-ground attack capability when it reached IOC in December 2005, and on Jan. 21, 2006, it flew its first operational sortie from Langley AFB, Va., as part of Noble Eagle.

Production aircraft have been delivered to operational units at Langley, Elmendorf, and Holloman, and are slated for Hickam. All F-22 squadrons will involve Total Force integration. As part of the Fiscal 2010 budget cuts announced April 6, 2009, the Pentagon plans to cap F-22 production at 187 aircraft, four more than the current program of record.

F-35 Lightning II

Brief: An affordable, highly common family of next generation strike aircraft.



F-35 Lightning II (Lockheed Martin photo)

Function: Multirole fighter.

Operator: ACC for USAF.

First Flight: Dec. 15, 2006 (F-35A prototype).

Delivery: 2009 (anticipated first production aircraft).

IOC: 2013 (USAF).

Production: planned: 1,763 (USAF), 680 total F-35B (USMC) and F-35C (USN), 150 (UK), more to eight development partner countries.

Inventory: TBD.

Unit Location: Planned: Edwards AFB, Calif.; Eglin AFB, Fla.; Hill AFB, Utah; Kadena AB, Japan; Nellis AFB, Nev.; Shaw AFB, S.C. ANG: McEntire ANGB, S.C.

Contractor: Lockheed Martin, with Northrop Grumman and BAE Systems; Pratt & Whitney is propulsion contractor; General Electric is second source engine contractor for the production phase.

Power Plant: currently one Pratt & Whitney F135, in 40,000-lb thrust class.

Accommodation: pilot only, on zero/zero ejection seat.

Dimensions: approx. span 35 ft, length 50.5 ft, height 17.3 ft.

Weight: TBD.

Ceiling: TBD.

Performance (design targets): mil power level speed at S/L, 630 knots calibrated airspeed (KCAS) for the F-35A conventional takeoff and landing (CTOL) variant (Mach 1 max power for CTOL only) and the F-35C carrier variant (CV), and 600 KCAS for the F-35B short takeoff and vertical landing (STOVL) aircraft, combat radius more than 590 miles for CTOL variant, 600 miles for CV, and 450 miles for STOVL.

Armament: 11 weapon stations (four internal, seven external), capable of carrying bombs up to 2,500 lb. The CTOL will have one internal 25 mm gun, the STOVL and CV variants will have the same weapon with an external missionized gun pod. Internal weapons bay: CTOL: two AIM-120Cs and two GBU-31 JDAMs. CV: two AMRAAMs and two GBU-31 JDAMs. STOVL: two AMRAAMs and two GBU-32 JDAMs. All variants will have internal and external GBU-12 and external AIM-9X. More than 30 stores are to be certified for carriage as system development continues.

COMMENTARY: The F-35 Lightning II Joint Strike Fighter is a multinational cooperative development program aimed at developing and fielding an affordable, highly common family of next generation strike fighters. For US forces, these comprise the F-35A CTOL version, the F-35B STOVL version for USMC, and F-35C CV carrier version for USN. USAF's F-35A will replace its current force of F-16 and A-10 aircraft with a stealthy multirole fighter that will comprise the bulk of USAF's fighter fleet for up to 50 years. This advanced multimission fighter is designed to penetrate high-threat enemy airspace and engage all enemy targets in any conflict. In addition to its advanced stealth design, the F-35 incorporates maneuverability, long range, and highly advanced avionics to accomplish the bulk of USAF missions. Its fully integrated avionics and weapons systems will permit simultaneous engagement of multiple targets in enemy airspace.

The system development and demonstration (SDD) phase, begun in October 2001, focuses on system development, test and evaluation, logistics support, and LRIP planning. A total of 18 test aircraft are being built, 12 for flight testing, six for nonairborne activities. Lockheed Martin completed assembly of the first F-35A flight-test aircraft in February 2006 and flight testing commenced Dec. 15, 2006. The final SDD aircraft are scheduled for completion 2009. Full-scale flight-test operations are planned to begin at Edwards AFB, Calif., in 2009, as well as delivery of the first production models for the joint training program at Eglin AFB, Fla.

The first flight by a USAF test pilot took place on Jan. 30, 2008. An F-35A achieved supersonic speed for the first time in November 2008. The first weight-optimized F-35A was rolled out on Dec. 19, 2008, the aircraft being structurally identical to the F-35s that will be delivered to the armed services beginning in 2010.

The F-35 is powered by the F135, a derivative of the Pratt & Whitney F119 engine. General Electric has been under contract to develop an interchangeable power plant, the F136, but the future for the alternative production engine is still unclear.

MQ-9 Reaper

Brief: A medium-to-high altitude, long-endurance remotely piloted UAV. Joint force commander multimission asset as a persistent hunter-killer against emerging targets.

Function: Unmanned attack and reconnaissance aircraft.

Operator: ACC.

First Flight: February 2001.

Delivered: November 2003.

IOC: FY07.

Production: 352 (planned).

Inventory: 22.

Unit Location: Creech AFB, Nev., Holloman AFB, N.M. (planned). ANG: Hancock Field, N.Y. (planned).

Contractor: General Atomics Aeronautical Systems.

Power Plant: one Honeywell TPE-331-10GDT turbo-prop engine.

Accommodation: unmanned system.

Dimensions: length 36.2 ft, span 66 ft.

Weight: empty 4,900 lb, gross 10,500 lb.

Ceiling: 30,000+ ft.

Performance: cruise speed 230 mph, endurance 14+ hours.

Armament: combination of AGM-114 Hellfire missiles, GBU-12/38 JDAM and GBU-49 Paveway II.

COMMENTARY

Officially combat-operational in Afghanistan since September 2007, the MQ-9 Reaper is larger than the MQ-1, has eight times the range, and flies twice as high. The typical MQ-9 system consists of several aircraft, a ground control station, communications equipment/links, spares, and active duty and/or contractor personnel. The crew is one pilot and one sensor operator. To meet combatant commanders' requirements, the MQ-9 delivers tailored capabilities using mission kits that may contain various weapons and sensors payload combinations.

The sensor suite for targeting includes a color/monochrome daylight TV, infrared, image intensified TV with a laser rangefinder/designator to precisely designate targets for laser guided munitions. The SAR enables GBU-38 JDAM targeting. The sensor is capable of very fine resolution in both spotlight and strip modes. The SAR also has ground moving target indicator capability.

YAL-1A Attack Airborne Laser

Brief: The prototype YAL-1A, using a modified 747-400F platform, is being developed as a boost-phase element of the ballistic missile defense system.

Function: Airborne laser.

Operator: ACC (projected).

First Flight: July 18, 2002 (Block 04 test bed).

Delivered: 2002.

IOC: TBD.

Production: TBD.

Inventory: TBD.

Unit Location: (Tail 1 prototype) Edwards AFB, Calif., (ABL system program office (SPO)) Kirtland AFB, N.M.

Contractor: Boeing (ABL platform; battle management (BM) system); Northrop Grumman (COIL and subsystems); Lockheed Martin (beam control system).

Power Plant: four GE CF6-80 turbofans, each 61,500 lb thrust.

Accommodation: flight crew of two, plus four mission specialists.

Dimensions: span 211.4 ft, length 228.8 ft, height 63.7 ft.

Weight: empty 423,882 lb, gross 800,000 lb.

Ceiling: 45,000 ft.

Performance: max operating speed Mach 0.83, unrefueled endurance at 40,000 ft with operational laser weapon load approx six hr.

Armament: megawatt-class COIL.

COMMENTARY

The Airborne Laser (ABL) is being developed by the Missile Defense Agency (MDA) as the first directed energy weapon in the US arsenal. Overall direction and budget authority for the program lies with MDA, while USAF continues to man and develop the program through its Airborne Laser System Program Office at Kirtland AFB, N.M.

Operational concepts call for ABLs to fly continuous patrols over deployed US forces, at an altitude of 40,000

ft. The aircraft would detect and shoot down any ballistic missiles launched at US forces or nearby allied nations. The ABL also would have the capability of determining hostile launch locations and passing that information to other US assets.

Central to the system is a Chemical-Oxygen Iodine Laser (COIL) system, running down the interior of the aircraft. Laser fire will emerge through a large ball turret in the nose. The system is designed to track ballistic missiles and maintain laser focus on their skin, which, when sufficiently heated, will cause the pressurized fuel within to explode.

The megawatt-class COIL technology can deliver high energy over a great distance largely because of its IR wavelength. In addition to the COIL, the ABL houses two other kilowatt-class lasers: the track illuminator laser, which produces more refined data, and the beacon illuminator laser, which measures atmospheric disturbance.

Following a two-year structural modification, the ABL platform's first flight took place July 18, 2002 from Boeing's Wichita, Kan., facility. A 10-month laser module test was completed in 2002, and, in December 2002, the platform was flown to Edwards AFB, Calif., for system installation. With YAL-1A in the hangar, tests were conducted independently on the ABL optical system and the six laser modules that make up the complete COIL system. All six modules were successfully tested on Nov. 10, 2004. The aircraft resumed airworthiness flight testing in December 2004, following installation of the beam control/fire-control system; performance demonstration of these systems was completed in August 2005. The aircraft was modified during 2006 to prepare for installation of the COIL, which was completed in early 2008. The integrated system is slated to begin flight testing in early 2009, working toward shutdown of a boosting ballistic missile in late 2009. Under DOD's Fiscal 2010 budget, plans were curtailed for a second ABL and YAL-1A relegated to research status only.

Reconnaissance and Surveillance Aircraft

E-3 Sentry

Brief: Heavily modified Boeing 707-320B aircraft, fitted with an extensive complement of mission avionics providing all-weather air surveillance and command, control, and communications for tactical and air defense forces.

Function: Airborne early warning, tactical battle management, and C2 of theater air forces.

Operator: ACC, PACAF, AFRC (assoc.).

First Flight: Oct. 31, 1975 (full avionics).

Delivered: March 1977-84.

IOC: 1977.

Production: 34.

Inventory: 32.

Unit Location: Elmendorf AFB, Alaska, Kadena AB, Japan, Tinker AFB, Okla. AFRC: Tinker AFB, Okla. (assoc.).

Contractor: Boeing; Northrop Grumman (radar); Lockheed Martin (computer).

Power Plant: four Pratt & Whitney TF33-PW-100/100A turbofans, each 21,000 lb thrust.

Accommodation: flight crew of four; 13-19 mission specialists.

Dimensions: span 145.8 ft, length 152.9 ft, height 41.5 ft.



MQ-9 Reaper (SSgt. James L. Harper Jr.)

Weight: gross 347,000 lb.
Capacity: 38,000 ft.

Performance: optimum cruise Mach 0.78, endurance eight hr unrefueled.

COMMENTARY

The E-3 Airborne Warning and Control System (AWACS) aircraft is capable of surveillance from Earth's surface up to the stratosphere, over land or water, at more than 200 miles. During conflict it will coordinate the actions of hundreds of strike, support, and cargo aircraft. As an integrated Air Force command control battle management (C2BM) surveillance, target detection, and tracking platform, AWACS is directly subordinate to the joint air operations center. Its extensive range of mission avionics enables it to provide an accurate real-time battlespace picture of friendly, neutral, and hostile activity; C2 for an area of responsibility; BM of theater forces; all-altitude/all-weather surveillance of the battlespace; and early warning of enemy actions.

AWACS may be employed alone or horizontally integrated with other C2BM and ISR elements. It provides the theater with the ability to find, fix, track, and target airborne or maritime threats and to locate and identify emitters. It can operate beyond the coverage of ground-based C2 and can exchange data with other C2 platforms and weapon systems.

E-3A. Of the 24 built for USAF in standard production configuration, 22 were later upgraded.

An improved US/NATO Standard E-3A configuration was initiated with the 25th USAF Sentry, delivered in December 1981, with a larger-memory computer and a maritime detection capability. Nine were built new for USAF, and one of the original E-3As was upgraded.

E-3B is the upgraded earliest version E-3A. Twenty-two product prototypes were produced. Improvements include much-enhanced computer capabilities, jam-resistant communications, austere maritime surveillance capability, additional radio communications, and five additional display consoles.

E-3C is an upgrade to the original 10 US/NATO Standard E-3A aircraft, with additional radio, console, and radar capabilities. Redelivered 1984.

A series of major sustainability, reliability, and availability upgrades for USAF E-3s has been undertaken to support the continuing demands on the system. The Block 40/45 upgrade is a major initiative for all 32 AWACS aircraft and will significantly enhance the Air Force's air BM/C2 capabilities for the 21st century battlefield. It will provide increased mission effectiveness for AWACS operators, improved reliability of the mission system, and lower life-cycle costs. Aging computer systems are being replaced by an open system local area network (LAN)-based architecture. Multisensor integration fuses on-board/off-board sensor systems and establishes a foundation for network-centric operations, producing better track quality, shortening the response time, and reducing operator/workload errors. AWACS net-centric mission systems will be complemented by the integration of advanced LOS and BLOS network communications links which will enable operators to interact with a broad range of information across the net-centric battlespace.

E-8 Joint STARS

Brief: A modified Boeing 707-300 series equipped with a large, canoe-shaped radome mounted under the forward part of the fuselage, housing long-range, air-to-ground radar capable of locating, classifying, and tracking vehicles moving on Earth's surface out to distances in excess of 124 miles.

Function: Ground surveillance, battle management (BM), C2 aircraft.

Operator: ACC and ANG, as the blended 116th Air Control Wing.

First Flight: December 1988.

Delivered: May 1996-present

IOC: Dec. 18, 1997.

Production: 18.

Inventory: 18.

Unit Location: Robins AFB, Ga.

Contractor: Northrop Grumman; Motorola; Cubic; Raytheon.

Power Plant: four Pratt & Whitney TF33-102C turbojets, each 19,200 lb thrust.

Accommodation: mission crew of 21 Air Force/Army operators (can be augmented to 34).

Dimensions: span 145.8 ft, length 152.9 ft, height 42.5 ft.

Weight: gross 336,000 lb.

Ceiling: 42,000 ft.

Performance: max operating speed Mach 0.84, endurance with one in-flight refueling 20 hr.

COMMENTARY

Joint STARS (Surveillance Target Attack Radar System) is a commercial Boeing 707-300 series platform extensively remanufactured and modified with radar, communications, operations, and control subsystems. A 27-ft-long canoe-shaped radome under the forward fuselage houses the 24-ft long-range, side-looking phased air-to-ground radar capable of locating, classifying, and tracking vehicles moving on Earth's surface. The antenna can be tilted to either side of the aircraft where it can develop a 120-degree field of

view covering nearly 19,305 square miles and is capable of detecting targets at more than 820,000 feet. Data is then transmitted via data link to ground stations or other aircraft.

It provides theater ground and air commanders with ground surveillance to support attack operations and targeting that contributes to the delay, disruption, and destruction of enemy forces. The weapon system is capable of providing commanders with transformational C2 and near-real-time wide area surveillance, ultimately passing targeting information to air and ground commanders. Joint STARS evolved from Army and Air Force programs to develop, detect, locate, and attack enemy armor at ranges beyond the forward area of troops. The first two developmental aircraft deployed in 1991 to Desert Storm and also supported Joint Endeavor in December 1995. Joint STARS supported NATO troops over Bosnia in 1996 and Allied Force in 1999. It continues to fly in support of Enduring Freedom and Iraqi Freedom. During the initial stages of Iraqi Freedom, E-8C Joint STARS aircraft were airborne 24 hours a day to help coalition forces maintain battlefield awareness.

E-8A. Prototype version, with specialized equipment installed aboard two specially modified 707-300 airframes. One was converted to an in-flight pilot trainer in 1997, and the second was scrapped.

E-8C. Production version, based on former commercial 707-300 airframes. Equipped with 18 operations and control consoles, two of which double as communications stations, all the aircraft have been modified to the more capable Block 20 aircraft, featuring more powerful computers and an Internet protocol local area network. The first E-8C became operational in 1996, and these aircraft are expected to remain airworthy until at least 2034. System improvements under way include enhancing Internet protocol (IP) connectivity with a beyond-line-of-sight (BLOS) capability; enhanced radar capabilities to improve tracking of land and sea targets through the Enhanced Land Maritime Mode (ELMM) Program; communications upgrades to address crypto, JTIDS, and broadcast intelligence equipment obsolescence; upgrades to the Prime Mission Equipment (PME) including radar signal processor and mission central computer and work station processor equipment; and communications navigation surveillance air traffic management upgrades to permit use of optimum altitudes and flight routes in increasingly congested commercial airspace. The process of re-engining the E-8C with improved performance Pratt & Whitney JT8D turbojets has begun, with the first operational aircraft expected to receive the new engines in late 2010.

MC-12W Liberty Project Aircraft (LPA)

Brief: A manned intelligence-surveillance-reconnaissance (ISR) version of the C-12, based on the Beechcraft King Air 350, providing near-real-time ISR to ground forces in Iraq and Afghanistan.

Function: Manned tactical ISR.

Operator: ACC.

First Flight: (King Air 350) September 1988.

Delivered: spring 2009 (planned).

IOC: May 2009 (planned).

Production: 37 (planned).

Inventory: 37 (planned).

Unit Location: Weapon system training at Meridian, Miss. (ANG).

Contractor: Hawker Beechcraft.

Power Plant: two Pratt & Whitney Canada PT6A-60A turboprops, each 1,050 shp.

Accommodation: two pilots and two sensor operators.

Dimensions: span 58 ft, length 46.7 ft, height 14.3 ft.
Weight: (King Air 350) gross 15,000 lb.

Ceiling: (King Air 350) 35,000 ft.

Performance: endurance: King Air 350 six hrs; King Air 350 ER 7.5 hrs.

COMMENTARY

The MC-12W Liberty Project Aircraft (LPA) is a modified sensor-equipped version of the C-12 aircraft based on the Beechcraft King Air 350. Thirty-seven are being acquired by USAF to augment existing overhead ISR assets operating in Iraq and Afghanistan, providing ground forces with high-value targeting data and other tactical intelligence. Modification includes full-motion video (FMV) and Sigint capabilities, data links to ground forces, a state-of-the-art countermeasures system, and a Blue-Force tracker. The first seven aircraft are modified, used King Air 350s; the remainder will be based on the King Air 350 Extended-Range model. Initial deployment is expected May 2009.

MQ-1 Predator

Brief: A medium-altitude, long-endurance unmanned aerial vehicle (UAV), flown remotely, providing joint force commanders with a multimission asset, by combining imagery sensors with strike capability.

Function: Armed reconnaissance, airborne surveillance, target acquisition.

Operator: ACC, AFSOC, ANG.

First Flight: July 1994.

Delivered: July 1994 (USAF from 1996)-present.

IOC: 2005.

Production: 186 air vehicles (objective force).

Inventory: 144.

Unit Location: Cannon AFB, N.M., Creech AFB, Nev., Holloman AFB, N.M. (planned), Nellis AFB, Nev. ANG: Ellington Field, Tex., Hector Arpt., N.D., March ARB, Calif.

Contractor: General Atomics Aeronautical Systems.

Power Plant: one Rotax 914F turbocharged engine.

Accommodation: unmanned system.

Dimensions: Block 5/10/15: length 27 ft, height 6.9 ft, span (Block 5) 48.7 ft, (Block 10/15), 55.2 ft.

Weight: empty 950 lb, gross 2,250 lb.

Ceiling: 25,000 ft.

Performance: cruise speed 80 mph, up to 138 mph, endurance 24 hr (460 miles with 16 hr on station).

Armament: Two Hellfire missiles.

COMMENTARY

The Predator UAV has evolved into a vital asset within USAF's warfighting inventory. A fully operational Predator system includes four air vehicles, a ground control station (GCS), satellite link, and about 55 personnel for 24-hour operations. The air vehicle crew comprises a pilot and a sensor operator.

DOD first used the advanced concept technology demonstration (ACTD) Predator in 1995 to support Provide Promise. USAF took over the Predator program in 1996 and in 1999 deployed the system operationally for surveillance missions over Bosnia and Iraq. The weapons capability was developed in response to lessons learned in the Balkans, and since 2002 Predators armed with laser guided Hellfire missiles have been used increasingly to attack targets in Afghanistan and Iraq. The RQ-1 designation was changed to MQ-1 to denote the multimission capability for both reconnaissance and strike. Currently, the Predator performs remote split operations by forward deploying launch and recovery GCS (LRGCS) aircraft and support personnel for takeoff and landing operations, while the CONUS-based GCS conducts the mission via extended communication links.



E-8C Joint STARS (Northrop Grumman photo)

MQ-1 is the multimission weaponized Predator A. It carries an MTS A sensor ball supplied by Raytheon in place of the Wescam sensor ball. The MTS A provides a laser target designator with EO/IR sensors in a single package. The SAR from the RQ-1 was removed. The MQ-1 can be controlled via direct line of sight or via satellite from a remote location. A new signals intelligence sensor payload (ASIP) is under development.

RQ-1A. The ACTD version of Predator A.

RQ-1B. The reconnaissance-only version of Predator A, with an internal 450-lb surveillance payload, including two EO and one IR video cameras carried in a ball-shaped turret under the nose and produced by Wescam. The internal sensor payload includes a SAR still imagery camera for a day/night, all-weather reconnaissance capability. USAF has retrofitted RQ-1Bs to MQ-1 configuration.

OC-135 Open Skies

Brief: A modified C-135 aircraft that flies unarmed observation and verification flights over nations that are parties to the 1992 Open Skies Treaty.

Function: Observation aircraft.

Operator: ACC.

First Flight: 1993.

Delivered: 1993-96.

IOC: October 1993.

Production: three.

Inventory: two.

Unit Location: Offutt AFB, Neb.

Contractor: Boeing.

Power Plant: four Pratt & Whitney TF33-P-5 turboprops, each 16,050 lb thrust.

Accommodation: seating for 35, incl cockpit crew, aircraft maintenance crew, foreign representatives, and crew members from the Defense Threat Reduction Agency.

Dimensions: span 131 ft, length 135 ft, height 42 ft.

Weight: gross 297,000 lb.

Ceiling: 50,000 ft (basic C-135).

Performance: speed: 500+ mph, unrefueled range 3,900 miles.

COMMENTARY

A modified version of the WC-135, used for specialized arms control treaty observation and imagery collection missions with framing and panoramic optical cameras installed in the rear of the aircraft.

OC-135B modifications include one vertical and two oblique KS-87E framing cameras, used for photography approximately 5,000 ft above the ground, and one KA-91C panoramic camera, which pans from side to side to provide a wide sweep for each picture, used for high-altitude photography up to approximately 35,000 ft. Data is processed and recorded by a recording and annotation system.

RC-26B

Brief: Specially configured variant of the Fairchild SA227-DC C-26 Metro 23 with surveillance and communications equipment for use primarily in counterdrug efforts but also increasingly for reconnaissance following natural and manmade disasters.

Function: Counterdrug-airborne day/night surveillance and C2.

Operator: ANG.

First Flight: not available.

Delivered: (C-26) first delivered 1989.

IOC: not available.

Production: 11.

Inventory: 11.

Unit Location: 11 locations in CONUS.

Contractor: Fairchild (airframe).

Power Plant: two Garrett TPE331-12UAR-701 turboprops, each 1,100 shp.

Accommodation: flight crew of two, one mission system operator; room for three law enforcement agents.

Dimensions: span 57 ft., length 59.5 ft, height 16.8 ft

Weight: max gross T-O 16,500 lb.

Ceiling: 25,000 ft.

Performance: speed 334 mph, range, 2,070 miles.

COMMENTARY

The RC-26B is a militarized version of the Fairchild Metro 23, modified as an ISR platform primarily in counterdrug operations. More recently, the aircraft have been used during natural disasters, such as hurricanes and wildfires, to provide real-time, streaming video footage to ground personnel handling the emergency, and during special national events to augment security operations. It also is supporting war on terror efforts abroad for US Central Command and US Southern Command.

Specialized equipment includes state-of-the-art digital aerial cameras and an infrared video camera. An extensive communications suite allows communications from 29-960 MHz, including provisions for plugging in 800 MHz handheld radios, and air phone capabilities.

RC-135

Brief: Specially configured variant of the Boeing C-135 Stratolifter, having an elongated nose and cheeks containing highly advanced electronic signal collection systems.



MQ-1 Predator (Lt. Col. Leslie Pratt)

Used to acquire real-time electronic and signals intelligence data for theater and tactical commanders.

Function: Electronic reconnaissance aircraft.

Operator: ACC.

First Flight: not available.

Delivered: circa 1973-99.

IOC: circa 1973 (Rivet Joint).

Production: (converted).

Inventory: 25.

Unit Location: Offutt AFB, Neb.

Contractor: Boeing (airframe); L3 Communications; Textron.

Power Plant: four CFM International F-108-CF-201 turboprops, each 24,000 lb thrust.

Accommodation: flight crew of three; 25-35 mission crew.

Dimensions: span 131 ft, length 140 ft, height 42 ft

Weight: max gross 299,000 lb.

Ceiling: 35,000 ft.

Performance: speed 500+ mph, range, with air refueling, unlimited.

COMMENTARY

The 55th Wing at Offutt AFB, Neb., operates a highly specialized fleet of RC-135s for worldwide reconnaissance missions. All are subject to ongoing modernization, with upgrade of avionics and primary mission equipment to expand capability and maintain effectiveness.

RC-135S Cobra Ball (CB). Cobra Ball collects measurement and signature intelligence (Masint) data, providing the capability to monitor missile-associated signal activity and to track missiles during boost and re-entry phases of flight. Cobra Ball can deploy anywhere in the world in 24 hours and provide on-scene EO reconnaissance for treaty verification and theater ballistic missile proliferation. Equipment includes wide-area IR sensors, long-range optical cameras, and an advanced communications suite.

RC-135U Combat Sent (CS). Each Combat Sent aircraft has a specifically designed signals intelligence (Sigint) suite used primarily to collect scientific and technical (S&T) electronic intelligence (Elint) data against air-, land-, and sea-based emitter systems. The accuracy of CS data is critical to the effective design, programming,

and reprogramming of radar warning receivers as well as jammers, decoys, and anti-radiation missiles and to the development of effective threat simulators.

RC-135V/W Rivet Joint (RJ). Rivet Joint is a self-contained standoff airborne signals intelligence (Sigint) collection system. Its primary role is to exploit the "electronic" battlefield and deliver near-real-time (NRT) intelligence-surveillance-reconnaissance (ISR) information to tactical forces, combatant commanders, and National Command Authorities across the full spectrum of conflict. Onboard collection capabilities encompass rapid search, detection, measurement, identification, demodulation, geolocation, and fusion of data from potentially thousands of electronic emitters.

TC-135S/W. Used for training purposes.

RQ-4 Global Hawk

Brief: A high-altitude, long-range, long-endurance UAV. **Function:** Unmanned surveillance and reconnaissance aircraft.

Operator: ACC, AFMC.

First Flight: Feb. 28, 1998.

Delivered: seven ACTD (no longer in inventory); seven Block 10, four Block 20, one Block 30 production aircraft.

IOC: ACTD system used operationally from November 2001 in Afghanistan and Iraq. Block 10s currently employed in CENTCOM theater.

Production: 54 (planned).

Inventory: 14.

Unit Location: Beale AFB, Calif., Grand Forks AFB, N.D. (planned), three forward operating bases planned for AFCENT, PACAF, and USAFE.

Contractor: Northrop Grumman (prime); Raytheon.

Power Plant: one Rolls Royce-North American AE 3007H turbofan, 7,600 lb thrust.

Accommodation: unmanned system.

Dimensions: RQ-4A (Block 10): length 44.4 ft, height 15.2 ft, span 116.2 ft; RQ-4B (Block 20/30/40): length 47.6 ft, span 130.9 ft.

Weight: gross RQ-4A: 25,600 lb; RQ-4B: 32,250 lb.

Ceiling: RQ-4A: 60,000+ ft; RQ-4B: up to 60,000 ft.



RQ-4 Global Hawk (USAF photo)



U-2S (John Tirpak)

Performance: endurance up to 28 hr. RQ-4A cruise speed 340 knots. RQ-4B cruise speed 310 knots.

Armament: none.

COMMENTARY

The RQ-4 provides high-altitude, persistent (28+ hours) remotely piloted ISR capability. The system consists of an aircraft, GCS, and an integrated sensor suite. The RQ-4 Global Hawk is being fielded in four distinctive blocks. Block 10 is in an imagery intelligence (Imint) configuration (EO/IR/SAR) and is basically a derivative of the ACTD aircraft successfully employed in Afghanistan and Iraq. Block 10s have flown operational missions supporting the war on terror. Block 20 (Imint) is larger; the first of six is expected to be operational in FY10. Block 30 (Multi-int) aircraft will add a high- and low-band signals intelligence (Sigint) capability to Block 20 Imint capability; fielding of 26 is projected from early FY12. Fifteen Block 40 multimission aircraft will provide radar Imint and BMC2 support with the Multiplatform Radar Technology Improvement Program (MP-RTIP) AESA sensor.

U-2 Dragon Lady

Brief: Single-seat, single-engine, high-altitude endurance reconnaissance aircraft carrying a wide variety of sensors and cameras, providing continuous day or night, high-altitude, all-weather area surveillance in direct support of US forces.

Function: High-altitude reconnaissance.

Operator: ACC.

First Flight: Aug. 4, 1955 (U-2); 1967 (U-2R); October 1994 (U-2S).

Delivered: 1955-October 1989.

IOC: circa 1956.

Production: 35 (U-2S/ST).

Inventory: 32.

Unit Location: Beale AFB, Calif.

Contractor: Lockheed Martin.

Power Plant: F118-GE-101 turbojet.

Accommodation: one (two for trainer).

Dimensions: span 103 ft, length 63 ft, height 16 ft.

Weight: gross 40,000 lb.

Ceiling: above 70,000 ft.

Performance: speed 475 mph; range more than 4,500 miles; max endurance 10+ hr.

COMMENTARY

The U-2 is the Air Force's premier high-altitude reconnaissance platform, capable of carrying Multi-int sensors simultaneously, currently making it USAF's only truly operational multi-intelligence platform, pending the introduction of later-block RQ-4 unmanned aerial vehicles (UAVs).

Although the U-2 was designed initially in the 1950s, current aircraft were produced primarily in the 1980s, when the production line was reopened to produce the TR-1, a significantly larger and more capable version than the earlier aircraft. Deliveries ended in October 1989.

U-2R (single-seat) and **U-2RT** (two-seat) aircraft. In 1992, all existing U-2s and tactical TR-1s were consolidated under the designation U-2R.

U-2S (single-seat) and **TU-2ST** (two-seat). The current designations of all aircraft in the inventory. Conversion to S model configuration began in October 1994. Included in the ongoing \$1.5 billion improvement program are new F118-GE-101 engines. Each current operational U-2 is now the Block 20 version with a new glass cockpit using multifunction displays (MFDs), a digital autopilot, and a new electronic warfare system. Sensor upgrades include the ASARS-2A SAR sensor, which provides enhanced imaging modes and improves geolocation accuracy; the SYERS-2 EO imagery system providing DOD's only multispectral and

IR capability; enhanced RF-intelligence capability; and new data links, enabling the U-2 to connect in near real time with network-centric hubs as well as line-of-sight ground stations, airborne data relays, and beyond-line-of-sight satellite data relays simultaneously. The optical bar camera (OBC) is also still in use, providing DOD's sole capability for broad-area synoptic imagery coverage.

NASA has two ER-2 versions of the U-2 used for high-altitude scientific experiments and atmospheric research, including investigation of global ozone depletion.

Special Duty Aircraft

E-4B National Airborne Operations Center

Brief: A four-engine, swept-wing, long-range high-altitude airplane providing a highly survivable command, control, and communications (C3) center allowing national/defense leaders to direct US forces, execute emergency war orders, and coordinate actions by civil authorities.

Function: Airborne operations center.

Operator: ACC.

First Flight: June 13, 1973 (E-4A); June 10, 1978 (E-4B).

Delivered: December 1974-85.

IOC: December 1974 (E-4A); January 1980 (E-4B).

Production: four.

Inventory: four.

Unit Location: Offutt AFB, Neb.

Contractor: Boeing; Rockwell; Raytheon E-Systems.

Power Plant: four General Electric CF6-50E2 turbofans, each 52,500 lb thrust.

Accommodation: up to 114 (63 crew/battle staff; 51 passengers).

Dimensions: span 195.7 ft, length 231.3 ft, height 63.4 ft.

Weight: gross 800,000 lb.

Ceiling: above 40,000 ft.

Performance: 6,900+ miles; unrefueled endurance in excess of 12 hr; with aerial refueling up to 72 hr.

COMMENTARY

A militarized version of the Boeing 747-200, **E-4B** aircraft perform the National Airborne Operations Center (NAOC)

mission. The E-4B fleet provides a survivable C3 platform throughout the full threat spectrum, including sustained operations in a nuclear environment. First operational mission was flown in March 1980.

E-4Bs are hardened against the effects of nuclear explosions, including electromagnetic pulse, and have in-flight refueling capability. A 1,200-kVA electrical system supports advanced system electronics as well as state-of-the-art communications and data processing equipment such as EHF Milstar satellite terminals and six-channel International Maritime Satellite (Inmarsat). A triband radome also houses the E-4B's superhigh frequency (SHF) frequency division multiple access (FDMA) communications antenna, the only such system on an airborne platform.

The E-4B system is capable of linking with commercial telephone and radio networks and could be used for radio broadcasts to the general population. E-4Bs also support the Federal Emergency Management Agency (FEMA).

In October 2006, the E-4B entered a new era when the first Modernization Block 1 (MB 1) upgrade aircraft reached IOC. MB 1 updates the electronic infrastructure supporting the aircraft's primary mission equipment and increases the bandwidth of external communications and onboard data transfer. These updates, along with changes to the aircraft's interior configuration, internal noise reduction modifications, BM improvements, and Global Air Traffic Management (GATM) avionics modifications, ensure the E-4B effectiveness for the foreseeable future. Three E-4B aircraft have received the MB 1 upgrade with the fourth and final aircraft scheduled for completion in 2010.

EC-130 Commando Solo

Brief: A heavily modified C-130 used for EW and electronic combat.

Function: psychological warfare.

Operator: ANG.

First Flight: January 1990.

Delivered: March 1990 (J model from 2003).

IOC: December 1990.

Production: no new-build EC-130E; seven (EC-130J).

Inventory: seven (EC-130J).

Unit Location: ANG: Harrisburg Arpt., Pa.

Contractor: Lockheed Martin; Raytheon; General Dynamics.

Power Plant: (EC-130E) T-56-A-1S turboprops, each 4,200 shp; (EC-130J) four Rolls Royce-Allison AE2100D turboprops, each 4,591 shp.

Accommodation: three flight crew, six mission (EC-130J).

Dimensions: EC-130J: span 132.6 ft, length 97.8 ft, height 38.9 ft.

Weight: EC-130J: gross 175,000 lb.

Ceiling: EC-130J: 30,500 ft.

Performance: speed 299 mph, range in excess of 2,100 miles; (C-130J) 393 mph, range 4,140 miles.

COMMENTARY

EC-130E ABCCC Airborne Battlefield Command and Control Center. Seven aircraft were updated by Unisys to ABCCC III standard. The advanced JTIDS received data transmitted by AWACS aircraft and other systems, enabling the crew to see a real-time picture of air operations over a combat area. Now retired.

EC-130E Commando Solo. Version used by the ANG as a broadcasting station for psychological warfare operations. Specialized modifications include enhanced navigation systems, self-protection equipment, and worldwide color television configuration. Replaced by EC-130J version.

EC-130J Commando Solo II. Specialized versions of the latest-model C-130 aircraft, ordered to replace E models, with current mission equipment transferred from the older E model Commando Solo aircraft. Entered service in 2004 with the 193rd SOW (ANG). Modifications include enhanced



EC-130J Commando Solo II (SSgt. Tia Schroeder)

navigation systems, additional self-protection equipment, air refueling, and the ability to broadcast radio and color TV on all worldwide standards.

Commando Solo aircraft have been used in every war and most contingency operations since 1980, supporting a broad spectrum of information operations and psychological operations missions.

EC-130H Compass Call

Brief: A heavily modified C-130 for electronic combat.
Function: Electronic warfare.

Operator: ACC.

First Flight: 1981.

Delivered: 1982.

IOC: 1983; (Block 30) February 1999.

Production: (converted).

Inventory: 14.

Unit Location: Davis-Monthan AFB, Ariz.

Contractor: Lockheed Martin.

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: standard crew 13, incl nine mission.

Dimensions: span 132.6 ft, length 99 ft, height 38 ft.

Weight: 155,000 lb.

Ceiling: 25,000 ft.

Performance: speed 374 mph at 20,000 ft.

COMMENTARY

The EC-130H Compass Call is designed to disrupt enemy C2 communications and limit adversary coordination essential for enemy force management. Modifications include electronic attack (EA) system and air refueling capability. Programmed upgrades will expand the EC-130H's mission by procuring a secondary EA capability against early warning and acquisition radars.

WC-130 Hercules

Brief: A high-wing, medium-range aircraft flown by AFRC for weather reconnaissance missions. It flies into the eye of tropical cyclones or hurricanes, collecting weather data from within the storm's environment.

Function: Weather reconnaissance aircraft.

Operator: AFRC.

First Flight: circa 1959.

Delivered: October 1999-2002.

IOC: 1959.

Production: no new-build WC-130H; 10 (WC-130J).

Inventory: 10 (WC-130H); 10 (WC-130J).

Unit Location: AFRC: Keesler AFB, Miss.

Contractor: Lockheed Martin.

Power Plant: WC-130J: four Rolls Royce AE2100D3 turboprops, each 4,500 shp.

Accommodation: six.

Dimensions: WC-130J: span 132.6 ft, length 97.8 ft, height 38.9 ft.

Weight: WC-130J: gross 175,000 lb.

Ceiling: WC-130J: 30,500 ft.

Performance: speed 374 mph at 20,000 ft.

COMMENTARY

The WC-130 is flown by AFRC's "Hurricane Hunters." The hurricane reconnaissance area includes the Atlantic Ocean, Caribbean Sea, Gulf of Mexico, and central Pacific Ocean areas.

WC-130B/E. Early version C-130 modified for weather reconnaissance. Now retired.

WC-130H. Later version C-130s modified for weather reconnaissance duties, equipped with two external 1,400-gallon fuel tanks, an internal 1,800-gallon fuel tank, and updated Allison T56-A-15 turboprops, each 4,910 shp.

The 10 WC-130H aircraft still counted in the inventory have been recycled for other operational uses.

WC-130J. Weather reconnaissance version of the most recent C-130 model, operated by the 53rd WRS for weather reconnaissance duties, including penetration of tropical storms, to obtain data for forecasting storm movements. Features include improved radar, four Rolls Royce AE2100D3 turboprops, and Dowty 391 six-bladed composite propellers.

An average weather reconnaissance mission might last 11 hours and cover almost 3,500 miles while the crew collects and reports weather data every minute. Results are transmitted via satellite to the National Hurricane Center, Miami.

Tanker Aircraft

HC-130N/P

Brief: An extended-range, combat search and rescue (CSAR)-configured C-130 that extends the range of rescue helicopters through in-flight refueling and performs tactical delivery of pararescue (PJ) specialists and/or equipment in hostile environments.

Function: Aerial refueling/transport.

Operator: ACC, AETC, ANG, AFRC.

First Flight: Dec. 8, 1964 (as HC-130H).

Delivered: from 1965.

IOC: 1966.

Production: (converted).

Inventory: 10 (HC-130N); 23 (HC-130P).

Unit Location: Active: Davis-Monthan AFB, Ariz., Kirtland AFB, N.M., Moody AFB, Ga. ANG: Francis S. Gabreski Arpt., N.Y., Kulis ANGB, Alaska. AFRC: Patrick AFB, Fla.

Contractor: Lockheed Martin.

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: four flight crew, plus mission crew.

Dimensions: span 132.6 ft, length 98.8 ft, height 38.5 ft.

Weight: gross 155,000 lb.

Ceiling: 33,000 ft.

Performance: speed 289 mph, range more than 4,000 miles.

COMMENTARY

The HC-130 can perform extended visual/electronic searches over land or water and operate from unimproved airfields. A three-man PJ team, trained in emergency trauma medicine, harsh environment survival, and assisted evasion, is part of the normal mission crew complement.

Combat air forces' HC-130 aircraft are equipped with an integrated GPS/INS navigation package, radar/missile warning receivers, and chaff/flare countermeasures dispensers. Some aircraft have FLIR systems and personnel locating systems (PLS) compatible with aircrew survival radios. Additional modifications include an improved digital low-power color radar, integrated satellite communications radio, NVG-compatible interior/exterior lighting, and cockpit armor. The C-130 Avionics Modernization Program (AMP) provides for complete update of the HC-130 avionics. Four retired EC-130E ABCCC and 10 WC-130H aircraft are being converted to HC-130 standard.

A new version, using new-build C-130J aircraft and based on the modified Marine Corps KC-130J, is being acquired, ultimately to replace the existing fleet of HC-130s and MC-130s used for combat search and rescue and special forces operations. AFSOC has a stated requirement for 115 of the new model.

KC-10 Extender

Brief: A modified McDonnell Douglas DC-10 that combines in a single aircraft the operations of aerial refueling and long-range cargo transport.

Function: Aerial refueling/transport.

Operator: AMC, AFRC (assoc.).

First Flight: April 1980.

Delivered: March 1981-April 1990.

IOC: August 1982.

Production: 60.

Inventory: 59.

Unit Location: Active and AFRC assoc.: McGuire AFB, N.J., Travis AFB, Calif.

Contractor: McDonnell Douglas (now Boeing).

Power Plant: three General Electric CF6-50C2 turbofans, each 52,500 lb thrust.

Accommodation: crew of four; additional seating possible for up to 75 persons with 17 pallets; max 27 pallets; max cargo payload 169,409 lb.

Dimensions: span 165.4 ft, length 181.6 ft, height 58.1 ft.

Weight: gross 593,000 lb.

Ceiling: 42,000 ft.

Performance: cruising speed Mach 0.825, range with max cargo 4,400 miles.

COMMENTARY

The KC-10 combines the tasks of tanker and cargo aircraft in a single unit, enabling it to support worldwide fighter deployments, strategic airlift, strategic reconnaissance, and conventional operations.

The KC-10 can be air refueled by a KC-135 or another KC-10, increasing its range and diminishing the need for forward bases, leaving vital fuel supplies in the theater of operations untouched.

KC-10A is a DC-10 Series 30CF, modified to include fuselage fuel cells, an air refueling operator's station, aerial refueling boom and integral hose reel/drogue unit, a receiver refueling receptacle, and military avionics. Wing-mounted pods enhance the aircraft's capabilities. Other modifications include the addition of communications, navigation, and surveillance equipment to meet civil air traffic control requirements.

Because it has both types of tanker refueling equipment installed, the KC-10A can service USAF, USN, USMC, and allied aircraft on the same mission. Special lighting permits night operations.

KC-135 Stratotanker

Brief: A short- to medium-range tanker aircraft, meeting the air refueling needs of USAF bomber, fighter, cargo, and reconnaissance forces. It also supports USN, USMC, and allied aircraft.

Function: Aerial refueling/airlift.

Operator: AETC, AFMC, AMC, PACAF, USAFE, ANG, AFRC.

First Flight: August 1956.

Delivered: January 1957-65.

IOC: June 1957, Castle AFB, Calif.

Production: 732.

Inventory: 37 (KC-135E); 363 (KC-135R); 54 (KC-135T).

Unit Location: Active: Altus AFB, Okla., Fairchild AFB, Wash., Grand Forks AFB, N.D., Kadana AB, Japan, MacDill AFB, Fla., McConnell AFB, Kan., RAF Mildenhall, UK, Robins AFB, Ga. Active and AFRC assoc.: Seymour Johnson AFB, N.C. Active and ANG assoc. (planned mid-2009): Birmingham Arpt, Ala., Pease ANGS, N.H., Scott AFB, Ill. ANG: from mid-2009 16 units. AFRC: seven units.

Contractor: Boeing.

Power Plant: KC-135R/T: four CFM International F108-CF-100 turbofans, each 22,224 lb thrust; KC-135E: four Pratt & Whitney TF33-PW-102 turbofans, each 18,000 lb thrust.

Accommodation: crew of four; up to 80 passengers.

Dimensions: span 130.8 ft, length 136.2 ft, height 38.3 ft.

Weight: empty 119,231 lb, gross 322,500 lb (KC-135E 301,600 lb).

Ceiling: 50,000 ft.

Performance: max speed at 30,000 ft 610 mph, range with max fuel 11,015 miles.

COMMENTARY

Mainstay of the USAF tanker fleet, the long-serving KC-135 is similar in size and appearance to commercial 707 aircraft but was designed to military specifications, incorporating different structural details and materials. The KC-135 fuel tanks are located in the "wet wings" and in fuel tanks below the floor in the fuselage.

KC-135A. Original version with J57 turbojets. USAF built 732, since modified to other standards.

KC-135E. The JT3D re-engining program upgraded USAF, AFRC, and ANG KC-135As to KC-135E standard with JT3D turbofans and related components removed from surplus commercial 707s; fuel carrying capacity increased by 20 percent. The E model is no longer actively flying but is maintained in such condition as to be available for service should the need arise.

KC-135R/T. Designation of re-engined KC-135A/Es with F108 turbofans. They embody modifications to 25 major systems and subsystems and not only carry more fuel



KC-135R Stratotanker, at right (MSgt. Kevin J. Gruenwald)



MC-130P Combat Shadow (SrA. Liliana Moreno)

farther but have reduced maintenance costs, are able to use shorter runways, and meet Stage III (noise abatement) requirements. The first KC-135R flight was in October 1982, and deliveries began in July 1984. KC-135T aircraft (formerly KC-135Q) were capable of refueling the now-retired SR-71s and retain the capability to carry different fuels in the wing and body tanks. Eight KC-135Rs are air refuelable. Twenty KC-135Rs have wing-mounted refueling pods for enhanced refueling of USN and NATO aircraft.

Ongoing modifications are extending the capability and operational utility of the KC-135 well into the 21st century. The Pacer CRAG avionics modernization program, completed in 2002, installed a new compass, radar, and GPS navigation systems, a traffic alert and collision avoidance system (TCAS), and new digital multifunctional cockpit displays. The Global Air Traffic Management (GATM) modification further improves the avionics, adding communications, navigation, and surveillance equipment ensuring access to reduced horizontal and vertical global airspace. Forty KC-135R/T aircraft are outfitted with the capability to relay Link 16 tactical information beyond line of sight of other aircraft.

MC-130P Combat Shadow

Brief: Aircraft that flies clandestine or low-visibility, low-level missions into denied areas to provide air refueling for special operations forces (SOF) helicopters or to air-drop small special operations teams, small bundles, and zodiac and combat rubber raiding craft.

Function: Air refueling for SOF helicopters/airdrop.

Operator: AETC, AFSOC, ANG, AFRC.

First Flight: Dec. 8, 1964 (as HC-130H).

Delivered: from 1965.

IOC: 1986.

Production: (converted).

Inventory: 27.

Unit Location: Active: Eglin AFB, Fla., Kadena AB, Japan, Kirtland AFB, N.M., RAF Mildenhall, UK. ANG: Moffett Field, Calif. AFRC: Duke Field, Fla.

Contractor: Lockheed Martin (airframe); Boeing.

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: four flight crew, plus four mission crew.

Dimensions: span 132.6 ft, length 98.8 ft, height 38.5 ft.

Weight: gross 155,000 lb.

Ceiling: 33,000 ft.

Performance: speed 290 mph, range with max normal payload 1,208 miles, unlimited with air refueling.

COMMENTARY

MC-130P Combat Shadow aircraft fly clandestine formation or single-ship intrusion of hostile territory missions to provide aerial refueling of special operations vertical-lift and tilt-rotor assets and the infiltration, exfiltration, and resupply of SOF by airdrop or air-land operations.

Recent modifications to the MC-130P feature improved navigation, communications, threat detection, and countermeasures systems. The Combat Shadow fleet has a fully integrated inertial navigation and Global Positioning System and night vision goggle-compatible interior and exterior lighting. It also has FLIR, radar and missile warning receivers, chaff and flare dispensers, NVG-compatible HUD, satellite and data-burst communications, as well as in-flight refueling capability as a receiver. Secondary capabilities include the ability to air-drop small teams, bundles, and rubber raiding craft. The aircraft are programmed to be modified with a cargo handling system by 2011 to provide the ability to handle palletized cargo and heavy equipment.

A new version, using new-build C-130J aircraft and based on the modified Marine Corps KC-130J, is being acquired, ultimately to replace the existing fleet of HC-130s and

MC-130s used for combat search and rescue and special forces operations. AFSOC has a stated requirement for 115 of the new model.

MC-130W Combat Spear

Brief: Aircraft that flies clandestine or low-visibility, low-level missions into denied areas to provide air refueling for special operations forces (SOF) helicopters or to air-drop small special operations teams, small bundles, and zodiac and combat rubber raiding craft.

Function: Air refueling for SOF vertical lift assets/airdrop.

Operator: AFSOC.

First Flight: Dec. 8, 1964 (as HC-130H).

Delivered: June 2006.

IOC: 2008.

Production: 12 (converted).

Inventory: six.

Unit Location: Cannon AFB, N.M.

Contractor: Boeing.

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: four flight crew, plus three mission crew.

Dimensions: span 132.6 ft, length 98.8 ft, height 38.5 ft.

Weight: gross 155,000 lb.

Ceiling: 33,000 ft.

Performance: speed 290 mph, range with max normal payload 1,208 miles, unlimited with air refueling.

COMMENTARY

Transferred from the 1st SOW at Hurlburt Field, Fla., in October 2007, the **MC-130W** is operated by the 73rd SOS at the redesignated 27th SOW at Cannon. The aircraft is a C-130H(2) airframe significantly modified to include an electronic warfare capability, low-light-level operational capability, and a strengthened tail to permit high-speed, low-level air-drop operations. The MC-130W is equipped with technically advanced refueling pods, providing the ability to refuel SOF helicopters and the CV-22. It also is capable of supporting limited command and control operations. The aircraft itself can be air refueled to extend its mission range. The MC-130Ws supplement AFSOC MC-130Hs lost in combat since the beginning of Enduring Freedom.

Strategic Transports

C-5 Galaxy

Brief: A heavy-lift, air refuelable cargo transport for massive strategic airlift over long ranges, including outside cargo. Supports special operations missions.

Function: Cargo and troop transport.

Operator: AMC, ANG, AFRC.

First Flight: June 30, 1968.

Delivered: October 1969-April 1989.

IOC: September 1970.

Production: 131.

Inventory: 59 (C-5A); 47 (C-5B); two (C-5C).

Unit Location: Active: Dover AFB, Del., Travis AFB, Calif. ANG: Eastern West Virginia Arpt., W.Va., Memphis Arpt., Tenn., Stewart Arpt., N.Y. AFRC: Dover AFB, Del. (assoc.), Lackland AFB, Tex., Travis AFB, Calif. (assoc.), Westover ARB, Mass., Wright-Patterson AFB, Ohio.

Contractor: Lockheed.

Power Plant: four General Electric TF39-GE-1C turbopfans, each 41,000 lb thrust. C-5M: four General Electric CF6-80C2 turbopfans.

Accommodation: normal crew of six (two pilots, two engineers, and two loadmasters), plus rest area for 15

(relief crew, etc.) and seating for 73. There is no piece of Army combat equipment the C-5 can't carry. Possible loads: six Apache helicopters, two M1 main battle tanks (each weighing 135,400 lb), six Bradley vehicles, three CH-47 helicopters, the 74-ton mobile bridge, a quarter-million pounds of relief supplies, or a maximum of 340 passengers in an airbus configuration. Air-drop capability for single platforms weighing up to 42,000 lb.

Dimensions: span 222.8 ft, length 247.9 ft, height 65.1 ft.
Weight: empty 374,000 lb, gross 769,000 (wartime 840,000) lb.

Ceiling: 45,000 ft.

Performance: max speed at 25,000 ft 571 mph, T-O run at S/L 8,300 ft, landing run, max landing weight at S/L 2,380 ft, range with max payload 3,434 miles, range with max fuel 7,245 miles. Normal cruising speed at altitude 518 mph (Mach 0.77).

COMMENTARY

One of the world's largest aircraft, the C-5 is able to carry unusually large and heavy cargo for intercontinental ranges at jet speeds. It can take off and land in relatively short distances and taxi on standard surfaces during emergency operations. Front and rear cargo openings permit simultaneous drive-through loading and off-loading.

C-5A. USAF took delivery of 81 of these basic models between December 1969 and May 1973. A major wing modification was subsequently undertaken, extending the aircraft's service life by 30,000 flight hours. Additionally, the avionics subsystems developed for the C-5B were incorporated into the C-5A fleet.

C-5B. Generally similar to the C-5A but embodies all the improvements introduced since completion of C-5A production, including the strengthened wings, improved turbopfans, and updated avionics, with color weather radar and triple INS. The first C-5B flew for the first time in September 1985 and was delivered to Altus AFB, Okla., in January 1986. To enhance force protection, a number of C-5Bs have been equipped with an aerial defense system.

C-5C. Two C-5As assigned to Travis AFB, Calif., were modified to carry outside space cargo for NASA by extending the cargo bay and modifying the aft doors.

C-5M Super Galaxy. Upgraded version of the C-5 featuring new avionics installed under the Avionics Modernization Program (AMP), to include a state-of-the-art cockpit and global access navigation safety compliance, plus new, higher performance GE CF6-80C2 turbopfans and additional components installed under the Reliability Enhancement and Re-engineering Program (RERP). The first of three production-representative C-5Ms made its debut flight on June 6, 2006. Developmental testing was successfully completed August 2008. The first of these three test aircraft was delivered to Warner Robins Air Logistics Center, Ga., in December 2008 and the other two to Dover AFB, Del., early 2009. Operational testing is expected to begin in the second half of 2009. USAF plans to upgrade 52 B and C models to C-5M configuration (three development aircraft and 49 production aircraft), with the remaining 59 older C-5As receiving only the AMP. Program completion is currently scheduled for 2017.

C-17 Globemaster III

Brief: A heavy-lift, air refuelable cargo transport for intertheater (strategic) and intratheater (tactical) direct delivery airlift of all classes of military cargo.

Function: Cargo and troop transport.

Operator: AETC, AFMC, AMC, PACAF, ANG, AFRC.

First Flight: Sept. 15, 1991.

Delivered: June 1993-ongoing.

IOC: Jan. 17, 1995.

Production: 205 (planned).

Inventory: 178.

Unit Location: Active: Altus AFB, Okla., Charleston AFB, S.C., Dover AFB, Del., Edwards AFB, Calif., Elmendorf AFB, Alaska, Hickam AFB, Hawaii, McChord AFB, Wash., McGuire AFB, N.J., Travis AFB, Calif. ANG: Allen C. Thompson Field, Miss., Elmendorf AFB, Alaska (assoc.), Hickam AFB, Hawaii (assoc.). AFRC: Charleston AFB, S.C. (assoc.), Dover AFB, Del. (assoc.), March ARB, Calif., McChord AFB, Wash. (assoc.), McGuire AFB, N.J. (assoc.), Travis AFB, Calif. (assoc.).

Contractor: Boeing.

Power Plant: four Pratt & Whitney F117-PW-100 turbopfans, each 40,440 lb thrust.

Accommodation: normal flight crew of three (two pilots plus loadmaster); additional pilot may be carried. Provisions for full range of military airlift missions, incl capacity for up to 189 passengers, 102 paratroops, or 36 litters; range of military cargo incl tanks and up to three AH-64A helicopters; three Bradley vehicles; one M1A2 main battle tank with other equipment; air-drop capability for single platforms weighing up to 60,000 lb; palletized passenger seats.

Dimensions: span over winglet tips 169.8 ft, length 173.9 ft, height 55.1 ft.

Weight: empty 277,000 lb, max payload 170,900 lb, gross 585,000 lb (extended range).

Ceiling: 45,000 ft.



C-17 Globemaster III (A1C Grovert Fuentes-Contreras)

Performance: normal cruising speed 484 mph at 35,000 ft or 518 mph (Mach .77) at 28,000 ft, unrefueled range with 160,000-lb payload 2,760 miles, additional 690 miles with extended-range fuel containment system (ERFCS), unlimited with refueling.

COMMENTARY

As the US military's core airlifter, the C-17 is able to operate routinely into small, austere airfields (3,000 ft x 90 ft) previously limited to C-130s and provides the only capability to air-land or air-drop outsize cargo directly to the tactical environment. C-17 aircraft have assumed the special operations low level (SOLL) mission previously supported by the C-141. They have flown numerous operational, humanitarian, and aeromedical evacuation missions since their introduction into the USAF inventory. The first C-17 operational strategic brigade airdrop occurred in March 2003, when a formation of 15 aircraft delivered a US Army brigade, complete with equipment, directly into northern Iraq.

C-17 is the first military transport to feature a full digital fly-by-wire control system and two-person cockpit, with two full-time, all-function HUDs and four multifunction electronic displays. Defensive systems include Large Aircraft Infrared Countermeasures (LAIRCM) and flares. Ongoing modernization, both through new block configuration to production aircraft and block upgrades to fielded aircraft, continues to improve C-17 operational capability. Significant improvements since 2001 include: (Block 12) ERFCS upgrade, a terrain awareness warning system (TAWS), and Mobility 2000 (M2K) C2 modernization program; (Block 15) a new Communications Open System Architecture (COSA) radio system; and (Block 16) a weather radar replacement. Block 17 marks the last block upgrade for the fleet; improvements include NVG-friendly combat lighting, upgraded electronic flight-control system, high frequency data link (HFDL), and formation flight system (FFS). Full retrofit up to Block 17 of previously delivered aircraft is planned for completion in 2018.

Under DOD's Fiscal 2010 budget, C-17 production is to stop at 205 aircraft.

COMMENTARY

C-9A. A derivative of the DC-9 Series 30 commercial airliner, the C-9A was the only USAF aircraft modified specifically for the aeromedical evacuation mission, a role now undertaken by C-130 and C-17 aircraft.

C-9C. Three specially configured C-9s, delivered to Andrews AFB, Md., in 1975 for the special air mission (SAM) supporting the President and other US government officials, are now in use by AFRC. Upgrades included improvements to the passenger communications equipment, GATM, TAWS, and vertical separation equipment.

C-12 Huron

Brief: Aircraft to provide airlift support for attache and military advisory groups worldwide.

Function: Special airlift.

Operator: AFMC, PACAF.

First Flight: Oct. 27, 1972 (Super King Air 200).

Delivered: 1974-late 1980s.

IOC: circa 1974.

Production: 88.

Inventory: 28.

Unit Location: Elmendorf AFB, Alaska, Yokota AB, Japan, various overseas embassies.

Contractor: Beech.

Power Plant: (C-12J) two Pratt & Whitney Canada PT6A-65B turboprops, each 1,100 shp.

Accommodation: crew of two; C-12C: up to eight passengers; C-12J: up to 19 passengers.

Dimensions: (C-12J) span 54.5 ft, length 43.8 ft, height 15 ft.

Weight: (C-12J) empty 9,850 lb, gross 16,600 lb.

Ceiling: (C-12J) 25,000 ft.

Performance: (C-12J) max cruising speed at 16,000 ft 307 mph, range with 10 passengers 1,806 miles.

COMMENTARY

The C-12 is a military version of the Beechcraft King Air A200 series.

C-12C. Re-engined C-12As, with PT6A-41 turboprops, deployed to overseas embassies.

C-12D. Similar to C model and also deployed to overseas embassies.

C-12F. With uprated PT6A-42 engines, can support medical airlift.

C-12J. A military version of the larger Beechcraft Model 1900, operated by PACAF.

C-20 Gulfstream

Brief: A twin-engine turboprop aircraft acquired to provide airlift for high-ranking government and DOD officials.

Function: Operational support airlift; special air missions.

Operator: AMC, USAFE.

First Flight: December 1979.

Delivered: September 1983-89.

IOC: circa 1983.

Production: not available.

Inventory: 10.

Unit Location: Andrews AFB, Md., Ramstein AB, Germany.

Contractor: Gulfstream.

Power Plant: C-20A/B: two Rolls Royce-Spey MK511-8 turboprops, each 11,400 lb thrust; C-20H: two Rolls Royce-Tay MK611-8 turboprops, each 13,850 lb thrust.

Accommodation: crew of five; 12 passengers.

Dimensions: span 77.8 ft; length (C-20A/B) 83.1 ft, (C-20H) 88.3 ft; height 24.3 ft.

Weight: C-20A/B gross 69,700 lb; C-20H gross 74,600 lb.

Ceiling: 45,000 ft.

Performance: max cruising speed 576 mph, range 4,800 miles.

COMMENTARY

C-20A. Three Gulfstream III transports were acquired to replace aging C-140B aircraft. They provided USAFE's operational support airlift fleet with intercontinental range and ability to operate from short runways. Retired in September 2002.

C-20B. Five C-20B versions, with advanced mission communications equipment and revised interior, were acquired in the late 1980s.

C-20H. Two Gulfstream IV SP aircraft, with advanced technology flight-management systems and upgraded Rolls Royce engines, were acquired by USAF to meet expanding SAM requirements. The two C-20H aircraft were reassigned to USAFE to replace retired C-20As.

Upgrade for C-20B/H aircraft includes GPS, vertical separation equipment, GATM, and TCAS.

C-21

Brief: Aircraft designed to provide cargo and passenger airlift and transport litters during medical evacuations.

Function: Pilot seasoning, passenger and cargo airlift.

Operator: AETC, AMC, USAFE, ANG.

First Flight: January 1973.

Delivered: April 1984-October 1985.

IOC: April 1984.

Production: 84.

Inventory: 57.

Unit Location: Keesler AFB, Miss., Ramstein AB, Germany, Scott AFB, Ill. ANG: Bradley Arpt., Mass., Buckley AFB, Colo., Hector Arpt., N.D., Mansfield Lahm Arpt., Ohio.

Contractor: Gates Learjet.

Power Plant: two AlliedSignal TFE731-2 turboprops, each 3,500 lb thrust.

Accommodation: crew of two and up to eight passengers or 3,153 lb cargo. Convertible to aeromedical evacuation configuration.

Dimensions: span 39.5 ft, length 48.6 ft, height 12.2 ft.

Weight: empty, equipped 10,119 lb, gross 18,300 lb.

Ceiling: 51,000 ft.

Theater and Special Use Transports

C-9 Nightingale

Brief: A twin-engine, medium-range, swept-wing jet aircraft used for DV duties.

Function: DV duties.

Operator: AFRC.

First Flight: August 1968.

Delivered: August 1968-February 1975.

IOC: circa 1968.

Production: 24.

Inventory: three (C-9C).

Unit Location: Scott AFB, Ill.

Contractor: Boeing (McDonnell Douglas).

Power Plant: two Pratt & Whitney JT8D-9A turboprops, each 14,500 lb thrust.

Accommodation: crew of three.

Dimensions: span 93.2 ft, length 119.2 ft, height 27.4 ft.

Weight: gross 108,000 lb.

Ceiling: 35,000 ft.

Performance: max cruising speed at 25,000 ft 565 mph, range 2,500 miles.



C-9C Nightingale (via Tom Kaminski)

Performance: max level speed at 25,000 ft 542 mph, range with max passenger load 2,306 miles, with max cargo load 1,653 miles.

COMMENTARY

C-21A aircraft provide operational support airlift for time-sensitive movement of people and cargo throughout the US and European Theaters, including aeromedical missions if required. Upgrades include GATM and TCAS. Older aircraft are being retired.

C-27J Spartan

Brief: A small tactical transport capable of carrying heavy loads into a wide range of airfields, including unprepared strips at high altitude.

Function: Tactical airlift.

Operator: USAF/USA.

First Flight: September 1999 (developmental aircraft).

Delivery: 2010 (USAF, planned).

IOC: TBD.

Production: 78 under contract: 24 (USAF); 54 (USA).

Inventory: TBD.

Unit Location: Active: TBD. ANG (announced): Hector Arpt., N.D., Mansfield Lahm Arpt., Ohio.

Contractor: L-3 Communications.

Power Plant: two Rolls Royce AE 2100-D2 turboprops, rated at 4,637 shp.

Accommodation: two flight crew; up to 68 troops or 24 paratroops, plus two loadmasters, or 36 litters plus

Power Plant: two Pratt & Whitney PW2040 turbofans, each 41,700 lb thrust.

Accommodation: 16 crew and 45 passengers.

Dimensions: span 124.8 ft, length 155.2 ft, height 44.5 ft.

Weight: empty 127,800 lb, gross 255,000 lb.

Ceiling: 41,000 ft.

Performance: cruise speed Mach 0.8-0.86 (530 mph), range 5,750 miles.

COMMENTARY

A military version of the commercial Boeing 757-200. The commercial DV interior includes a crew rest area, DV stateroom, conference area, and general passenger area. The passenger communications system provides worldwide clear and secure voice and data communications. Modern flight deck avionics allow operations to any suitable airfield in the world and provide an upgrade path as new capabilities become available. Upgrades include installation of a digital communications management system and broadband data transmit and receive, providing an office-in-the-sky capability.

C-37

Brief: Modified Gulfstream aircraft utilized as part of the executive fleet, providing transportation for the vice president, Cabinet, Congressional members, Secretary of Defense, service Secretaries, and other prominent US and foreign officials.

Function: VIP air transport.

The **C-37B** is a military version of the Gulfstream 550, modified for VIP duties. Major differences from the C-37A are the Honeywell PlaneView flight deck and increased range. Upgrades include a directional IR countermeasures system. The one C-37B is assigned to the 89th AW at Andrews.

C-38A

Brief: A twin-engine transcontinental aircraft used to provide transportation for DVs such as Congressional or high-ranking military members. It can also be configured for medevac and a wide range of special missions including C3 in time of war.

Function: VIP air transport and operational support.

Operator: ANG.

First Flight: 1998.

Delivered: April-May 1998.

IOC: 1998.

Production: two.

Inventory: two.

Unit Location: Andrews AFB, Md.

Contractor: Tracor (Israel Aircraft Industries Ltd).

Power Plant: two AlliedSignal TFE731-40R-200G, each 4,250 lb thrust.

Accommodation: typically two crew and eight passengers. In medevac role: two Spectrum 500 Life Support Units and two medical attendants. All seats removable for cargo.

Dimensions: span 54.6 ft, length 55.6 ft, height 18.2 ft.

Weight: gross 24,800 lb.

Ceiling: cruise, 33,000 ft.

Performance: cruise speed Mach 0.87.

COMMENTARY

The **C-38A** is a military version of the Astra SPX produced by IAI and supported worldwide by Galaxy Aerospace. Equipment includes the most up-to-date navigation, communication, vertical separation, and safety equipment as well as state-of-the-art avionics.

C-40

Brief: A Boeing 737-700 used for medium-range airlift of personnel.

Function: Passenger transportation.

Operator: AMC, PACAF, USAF, ANG, AFRC.

First Flight: USN C-40A: April 14, 1999.

Delivered: 2002.

Production: 10.

Inventory: 10.

Unit Location: Andrews AFB, Md., Hickam AFB, Hawaii, Ramstein AB, Germany. ANG: Andrews AFB, Md. AFRC: Scott AFB, Ill.

Contractor: Boeing.

Power Plant: two General Electric CFM56-7 turbofans, each 24,000 lb thrust.

Accommodation: flight crew of four, plus three or four cabin crew; up to 89 passengers.

Dimensions: span 112 ft 7 in, length 110 ft 4 in, height 41 ft 2 in.

Weight: gross 171,000 lb.

Ceiling: 41,000 ft.

Performance: cruise speed 0.78-0.82 Mach, range 3,450 miles.

COMMENTARY

The C-40 is the military version of the commercial Boeing 737-700 increased gross weight aircraft. C-40s are used for transporting senior government officials and regional combat commanders.

C-40B. The B model is equipped with a DV suite, staff work area, conference area, and worldwide secure communications and data capability. USAF purchased three and leased one C-40B. Two are assigned to Andrews and one each to Hickam and Ramstein.

C-40C. The C model has a DV seating area, general passenger seating area, and secure communications capability. Three C-40Cs are operated by ANG's 201st Airlift Squadron from Andrews, and three by AFRC's 932nd AS at Scott.

C-130 Hercules

Brief: A rugged aircraft capable of operating from rough dirt strips to provide theater airlift and paratropping of troops and equipment into hostile areas.

Function: Inter- and intratheater airlift.

Operator: AETC, AFSOC, AMC, PACAF, USAF, ANG, AFRC.

First Flight: August 1954 (C-130A).

Delivered: December 1956-present (C-130J).

IOC: circa 1958.

Production: more than 2,200.

Inventory: 96 (C-130E); 280 (C-130H); 51 (C-130J).

Unit Location: Active: Dyess AFB, Tex., Hurlbert Field, Fla., Little Rock AFB, Ark., Pope AFB, N.C., Ramstein AB, Germany, Yokota AB, Japan. ANG: 22 units. AFRC: nine units. AFRC/ANG assoc.: one.

Contractor: Lockheed Martin.

Power Plant: (C-130H) four Rolls Royce-Allison T56-A-15 turboprops, each 4,300 shp. (C-130J) four Rolls Royce-Allison AE2100D3 turboprops, each 4,591 shp.

Accommodation: (C-130H) crew of five; up to 92 ground



C-130 Hercules (TSgt. Jeremy Lock)

six attendants; up to 25,353 lb cargo; 19,842 lb low velocity airdrop.

Dimensions: (basic G.222 airframe) span 94.1 ft, length 74.5 ft, height 32.1 ft.

Weight: gross 70,000 lb.

Ceiling: 30,000 ft.

Performance: T-O run 1,903 ft; range, with 22,046 lb payload 1,000 nm.

COMMENTARY

In June 2007, the Air Force and Army selected the **C-27J** Spartan, a derivative of the Alenia G.222, to fulfill the Joint Cargo Aircraft (JCA) requirement. Plans call initially for 78 aircraft. USAF will use its aircraft to support ground forces served only by the most basic airstrips, often at high altitude, or for missions where the C-130 is currently operating at half-load capacity.

The Air Force also is considering purchasing additional C-27s to function in a gunship role with AFSOC. The currently planned buy is expected to go primarily to ANG units.

C-32

Brief: A modified Boeing 757-200 used to provide backup transportation for the President. It is the primary means of travel for the vice president, Cabinet, Congressional members, and other high-ranking US and foreign officials.

Function: VIP air transport.

Operator: AMC, ANG.

First Flight: Feb. 19, 1982 (USAF Feb. 11, 1998).

Delivery: June-December 1998.

IOC: 1998.

Production: six.

Inventory: six.

Unit Location: Andrews AFB, Md. ANG: McGuire AFB, N.J.

Contractor: Boeing.

Operator: AMC, PACAF, USAF.

First Flight: USAF October 1998.

Delivery: October 1998-present.

IOC: Dec. 9, 1998.

Production: 10 (C-37A); one (C-37B).

Inventory: nine (C-37A); one (C-37B).

Unit Location: Andrews AFB, Md., Chievres, Belgium, Hickam AFB, Hawaii, MacDill AFB, Fla.

Contractor: Gulfstream.

Power Plant: two BMW-Rolls Royce BR710A1-10 turbofans, each 14,750 lb thrust.

Accommodation: five crew and 12 passengers.

Dimensions: span 93.5 ft, length 96.4 ft, height 25.8 ft.

Weight: empty 47,601 lb, gross 90,500 lb.

Ceiling: 51,000 ft.

Performance: cruise speed Mach 0.8 (530 mph), range 6,095 miles.

COMMENTARY

The **C-37A** is a military version of the Gulfstream V. Two C-37As, along with the C-32s, were purchased as replacements for VC-137B/C aircraft. The interior includes separate DV and passenger areas and a communications system capable of worldwide clear and secure voice and data. Aircraft are capable of operations at any suitable civilian or military airfield worldwide. A third C-37A was purchased for combat commander support airlift and was based initially at Chievres, Belgium, but subsequently reassigned to Andrews AFB, Md. One C-37 was purchased for crisis response support. Five C-37As are being leased from Gulfstream Aerospace as combat commander support aircraft; three are assigned to MacDill AFB, Fla.; one to Chievres; and one to Hickam AFB, Hawaii. Upgrades include GATM and continuing passenger communications system upgrades to the Andrews-based aircraft.

troops, 64 paratroops, 74 litter patients plus attendants, 54 passengers on palletized seating, or up to five 463L standard freight pallets, etc.; max load, 45,000 lb.

Dimensions: span 132.6 ft, length 97.8 ft, height 38.1 ft.

Weight: C-130H: empty 81,000 lb, fuel/cargo max gross 155,000 lb; C-130J: gross 175,000 lb.

Ceiling: 33,000 ft at 100,000 lb T-O weight.

Performance: (C-130H) max cruising speed 430 mph, T-O run 3,585 ft, landing run (at 130,000 lb) 1,700 ft, range with 40,000-lb payload 2,240 miles; range 3,450 miles.

COMMENTARY

With deliveries worldwide spanning more than 50 years, the C-130 Hercules transport continues in production. Basic and specialized versions operate throughout USAF, performing diverse roles in both peace and war situations, including airlift support, Arctic ice cap resupply, aeromedical missions, aerial spray missions (AFRC), fire-fighting duties (AFRC and ANG) for the US Forest Service, and natural disaster and humanitarian relief missions.

C-130A, B, and D. Early versions, now retired. The initial production C-130A had four Allison T56-A-11 or -9 turboprop engines. USAF ordered a total of 219. The C-130B had improved range and higher weights and introduced Allison T56-A-7 turboprops; 134 were produced, with delivery from April 1959. Twelve were modified beginning 1961 as **JC-130Bs** for air-snatch satellite recovery together with three early H models. Twelve C-130Ds were modified as for Arctic operations.

C-130E is an extended-range development of the C-130B, with large under-wing fuel tanks; 389 were ordered, with deliveries beginning in April 1962. A wing modification to correct fatigue and corrosion extended the life of the aircraft well into this century. Other modifications include a self-contained navigation system, with an integrated communications/navigation management suite, GPS capability, and a state-of-the-art autopilot that incorporates a ground collision avoidance system. USAF is retiring some of the older aircraft. AFSOC retains some C-130Es for aviation advisory aircraft flight proficiency.

C-130H is generally similar to the E model but has updated turboprops, a redesigned outer wing, and improved pneumatic systems; delivery began in July 1974. Subsequent improvements include updated avionics, improved low-power color radar, and other minor modifications. Night vision instrumentation system was introduced from 1993, TCAS II in new aircraft from 1994. ANG **LC-130H** aircraft are modified with wheel-ski gear to support Arctic and Antarctic operations. Two **DC-130Hs** were modified for UAV control duties.

A major AMP for the C-130 includes digital displays, flight-management systems, multifunction radar, new communications systems, and a single air data computer. Planned completion is for 2016. The AMP upgrade includes all C-130 models except the C-130E, older or worn-out C-130Hs, and the new C-130J aircraft. In addition, work has begun to replace wing boxes on 155 C-130s in a move to alleviate/pre-empt operational restrictions; completion is planned for 2020. Some 600 C-130s will also receive landing gear modifications beginning in 2010.

C-130J. Most recent model featuring a three-crew flight operation system, 6,000 shp Rolls Royce-Allison AE2100D engines, all composite six-blade Dowty Aerospace R391 propeller system, digital avionics, and mission computers. Compared to earlier production C-130Es, its speed is up 21 percent, cruising altitude is 40 percent higher, and range 40 percent longer. The J also features improved reliability and maintainability. ANG and AFRC units began receiving J models in 1999. First active duty unit, the 48th AS at Little Rock AFB, Ark., received its first C-130J aircraft in March 2004. First wartime deployment occurred December 2004, although official IOC was only declared in October 2006. The stretch version of the C-130J (**C-130J-30**), with an additional 15 feet of fuselage and capable of carrying up to 128 ground troops or 92 paratroops, is replacing the oldest 1960s-vintage C-130Es. Deliveries to ANG began in 2001 and to USAF and AFRC in 2004. Current plans include purchase of 117 C-130J combat-delivery aircraft.

CV-22

Brief: A tilt-rotor, multimission transport aircraft designed to have the maneuverability and lift capability of a helicopter and the speed of a fixed-wing aircraft.

Function: Multimission airlift.

Operator: AETC, AFSOC.

First Flight: March 19, 1989 (V-22).

Delivery: 2006.

IOC: 2009 (planned).

Production: 50 (planned).

Inventory: 10.

Unit Location: Hurlburt Field, Fla., Kirtland AFB, N.M.

Contractor: Bell Boeing; Raytheon.

Power Plant: two Rolls Royce-Allison AE1107C turbo-shafts, each 6,200 shp.

Accommodation: four (two pilots, two flight engineers); additional pilot for extended duration missions; up to 18 troops or 8,000 lb internal cargo.

Dimensions: proprotor diameter 38 ft, width, rotors turn-



CV-22 Osprey (SrA. Julianne Showalter)

ing 84.6 ft, fuselage length 57.3 ft, height 22 ft.

Weight: gross weight 34,900 lb, max VTO 52,870 lb; STO 57,000 lb, self-deploy T-O 60,500 lb.

Ceiling: 26,000 ft.

Performance: typically will carry troops or cargo over a 500-mile combat radius at 265 mph. Self-deployment range with one air refueling 2,417 miles.

COMMENTARY

CV-22 is the designation for the US Special Operations Command variant of the V-22 Osprey. The CV-22 is a multi-engine, dual-piloted, self-deployable, medium-lift vertical takeoff and landing (VTOL) tilt-rotor aircraft for the conduct of special operations, including nuclear, biological, and chemical (NBC) warfare conditions. It is designed to operate from land bases and austere forward operating locations, as well as air capable ships without reconfiguration or modification. An in-flight refueling capability extends combat mission range when required, and the aircraft is self-supporting to the maximum practical extent. The CV-22's mission is long-range clandestine penetration of denied areas in adverse weather and low visibility to infiltrate, exfiltrate, and resupply SOF.

CV-22 avionics include a fully integrated precision navigation suite, with GPS and INS; a digital cockpit management system oriented around four multifunction displays (MFDs); FLIR; an integrated NVG HUD; terrain-following/terrain-avoidance (TF/TA) radar; and digital map system. Additionally, it is equipped with robust self-defensive avionics and secure anti-jam, redundant communications compatible with current and planned systems used by command and control agencies and ground forces. The CV-22 unrefueled combat range satisfies current and emergent major theater war (MTW) requirements, as well as national mission tasking. The aircraft is capable of completing most assigned missions during one period of darkness.

A third aircraft joined the two test aircraft based at Edwards AFB, Calif., in February 2005. The first production example was delivered to USAF in September 2005 and the first combat-configured aircraft in March 2006. Operational utility evaluation was completed in summer 2006 and flight crew training began in late 2006 at Kirtland AFB, N.M. The first operational CV-22 squadron, the 8th SOS at Hurlburt Field, Fla., received its first aircraft in January 2007. IOT&E was completed by summer 2008. In November 2008, four Ospreys from the 1st SOW deployed to Mali, Africa, in support of Exercise Flintlock, marking the CV-22's first operational deployment. USAF may place detachments of CV-22s in US European Command and US Pacific Command theaters.

MC-130E/H Combat Talon

Brief: A modified C-130 able to provide global, day, night, and adverse weather capability to air-drop personnel and to deliver personnel and equipment to support US and allied SOF.

Function: SOF infiltration, exfiltration, and resupply.

Operator: AETC, AFSOC, AFRC.

First Flight: circa 1965 (MC-130E); January 1990 (MC-130H).

Delivered: initially 1966.

IOC: 1966 (MC-130E); June 1991 (MC-130H).

Production: 22 new-build MC-130Hs.

Inventory: 14 (MC-130E); 20 (MC-130H).

Unit Location: Active (assoc.) and AFRC MC-130Es at Duke Field, Fla. Active: MC-130H at Hurlburt Field, Fla., Kadena AB, Japan, Kirtland AFB, N.M., RAF Mildenhall, UK.

Contractor: Lockheed Martin (airframe); Boeing integrated weapons system support.

Power Plant: four Allison T56-A-15 turboprops, each 4,910 shp.

Accommodation: MC-130E: crew of nine; 53 troops or 26 paratroops; MC-130H: crew of seven; 77 troops, 52 paratroops, or 57 litters.

Dimensions: span 132.7 ft, height 38.6 ft, length 100.8 ft (MC-130E), 99.8 ft (MC-130H).

Weight: empty 72,892 lb, gross 155,000 lb.

Ceiling: 30,000 ft.

Performance: max speed 289 mph, range 3,110 miles, unlimited with refueling.

COMMENTARY

MC-130 Combat Talon aircraft are equipped with terrain-following and terrain-avoidance radars, precision navigation systems using INS/GPS, and electronic and infrared countermeasures for self-protection. Both E and H aircraft are capable of in-flight refueling, are NVG-compatible, and have a modified tail empennage for their high-speed aerial delivery system. The primary mission of the aircraft is to conduct infiltration, resupply, and exfiltration of special operations forces (SOF). They are also capable of supporting psychological operations. Combat Talons are able to air-drop or to land on austere unmarked landing or drop zones.

MC-130E Combat Talon I. Fourteen modified C-130E aircraft were additionally equipped with a pod-based system to air refuel SOF helicopters and tilt-rotor aircraft.

MC-130H Combat Talon II. C-130H(2) aircraft modified with an integrated glass cockpit were acquired in the late 1980s and early 1990s to supplement the Combat Talon Is. All are modified with a state-of-the-art pod-based aerial refueling system to augment the MC-130E and MC-130P aerial refueling fleet. The 1st, 7th, and 15th SOSs provide support to SOF in Europe, the Pacific, and CONUS, respectively. The 58th SOS at Kirtland AFB, N.M., is responsible for MC-130H mission qualification training.

VC-25 Air Force One

Brief: A specially configured Boeing 747-200B used for air transport of the President and his entourage. When the President is aboard, it has the radio call sign "Air Force One."

Function: Air transport of the President.

Operator: AMC.

First Flight: first flown as Air Force One Sept. 6, 1990.

Delivered: August-December 1990.

IOC: circa 1990.

Production: two.

Inventory: two.

Unit Location: Andrews AFB, Md.

Contractor: Boeing.

Power Plant: four General Electric CF6 turbofans, each 56,700 lb thrust.

Accommodation: crew of 26; up to 76 passengers.

Dimensions: span 195.7 ft, length 231.8 ft, height 63.4 ft.

Weight: long-range mission T-O weight 803,700 lb., gross 833,000 lb.

Ceiling: 45,000 ft.

Performance: speed 630 mph (Mach 0.92), normal cruising speed Mach 0.84, unrefueled range 7,820 miles.

COMMENTARY

Based on the Boeing 747-200B airframe, two **VC-25As** assigned to Andrews AFB, Md., support the President. Aircraft are equipped with staff work areas, a conference room, a general seating area, and an executive office.

Communications capability includes worldwide secure and clear communications equipment. Upgrades include GATM and installation of a broadband data transmit and receive capability to provide video teleconferencing and office-in-the-sky capability.

Trainer Aircraft

T-1A Jayhawk

Brief: A medium-range, twin-engine jet trainer version of the Beechcraft 400A. It is used by the Air Force to train student airlift and tanker pilots and student combat systems operators.

Function: Advanced pilot training.

Operator: AETC, AFRC, USN.

First Flight: Sept. 22, 1989 (Beechcraft 400A).

Delivered: Jan. 17, 1992-July 1997.

IOC: January 1993.

Production: 180.

Inventory: 179.

Unit Location: Active: Columbus AFB, Miss., Laughlin AFB and Randolph AFB, Tex., Vance AFB, Okla., NAS Pensacola, Fla. (forward operating station). AFRC: Randolph AFB, Tex. (assoc.).

Contractor: Raytheon.

Power Plant: two Pratt & Whitney Canada JT15D-5B turboprops, each 2,900 lb thrust.

Accommodation: two, side by side, and one to the rear; rails are fitted to accommodate an extra four seats to permit transport of maintenance teams.

Dimensions: span 43.5 ft, length 48.4 ft, height 13.9 ft.

Weight: empty 5,200 lb, gross 16,100 lb.

Ceiling: 41,000 ft.

Performance: max speed at 27,000 ft 538 mph, range 2,400 miles.

COMMENTARY

The swept-wing T-1A Jayhawk is a military version of the Beech 400A used in the advanced phase of joint specialized undergraduate pilot training (JSUPT) for students selected to go on to fly tanker, transport, and electronic warfare aircraft. It is also used to train student combat systems operators (CSO) and naval flight officers in the intermediate stages of their training.

The T-1A has cockpit seating for an instructor and two students. Special mission equipment includes GPS, an electronic flight instrument system (EFIS) avionics system, a single-point refueling system, an additional fuselage fuel tank, and increased bird-strike protection in the windshield and leading edges for sustained low-level operation. T-1As typically log 100,000 flying hours a year, supporting all-weather training operations at high and low altitudes.

T-6A Texan II

Brief: A single-engine turboprop aircraft used for training student pilots, combat systems officers, and naval flight officers in fundamentals of aircraft handling and instrument, formation, and night flying.

Function: Primary trainer.

Operator: AETC, AFRC, USN.

First Flight: July 15, 1998.

Delivery: May 2000-present (operational aircraft).

IOC: November 2001.

Production: Planned: 372 (USAF); 328 (USN).

Inventory: 354 (USAF).

Unit Location: USAF: Active: Columbus AFB, Miss.,



T-1A Jayhawk (Lt. Col. Russell Hopkinson)

Laughlin AFB and Randolph AFB, Tex., Vance AFB, Okla. Planned: Sheppard AFB, Tex. USN: NAS Corpus Christi, Tex., NAS Whiting, Fla.

Contractor: Hawker Beechcraft (formerly Raytheon).

Power Plant: one Pratt & Whitney Canada PT6A-68 turboprop, 1,100 shp.

Accommodation: two, in tandem, on zero/zero ejection seats.

Dimensions: span 33.5 ft, length 33.4 ft, height 10.7 ft.

Weight: empty (approx) 4,707 lb; gross 6,500 lb.

Ceiling: 31,000 ft.

Performance: max speed 368 mph, range 920 miles.

COMMENTARY

The Joint Primary Aircraft Training System (JPATS) T-6A Texan II is based on the Swiss Pilatus PC-9 aircraft, modified to include a strengthened fuselage, zero/zero ejection seats, increased aircrew accommodation, upgraded engine, increased fuel capacity, pressurized cockpit, larger, bird-resistant canopy, and new digital avionics. The JPATS replaces USAF's T-37Bs and USN's T-34Cs in primary pilot training, as well as supporting undergraduate naval flight officer and USAF combat systems officer training.

T-37 Tweet

Brief: A twin-engine jet aircraft used for training undergraduate pilots in fundamentals of aircraft handling and instrument, navigation, formation, and night flying.

Function: Primary trainer.

Operator: AETC.

First Flight: September 1955.

Delivered: December 1956-68.

IOC: 1957.

Production: 985.

Inventory: 32.

Unit Location: Sheppard AFB, Tex.

Contractor: Cessna.

Power Plant: two Continental J69-T-25 turbojets, each

1,025 lb thrust.

Accommodation: two, side by side, on ejection seats.

Dimensions: span 33.7 ft, length 29.2 ft, height 9.1 ft.

Weight: empty 3,870 lb, gross 6,625 lb.

Ceiling: 35,000 ft.

Performance: max speed at S/L 315 mph, range 460 miles.

COMMENTARY

USAF's first purpose-built jet trainer, the T-37 has been AETC's standard two-seat primary trainer for several decades. Its distinctive blue-and-white finish is intended to help formation training and ease maintenance.

T-37A, with J69-T-9 turbojets; all have been modified to T-37B standards.

T-37B. The original T-37A was superseded in November 1959 by the T-37B, with improved radio navigational equipment, UHF radio, and upgraded instruments. Kits were subsequently produced to extend the capability of the T-37 by modifying or replacing critical structural components. AETC has been replacing the T-37B with the T-6A Texan II since 2000.

T-38 Talon

Brief: A twin-engine, high-altitude, supersonic jet trainer used in a variety of roles, primarily for undergraduate pilot, pilot instructor training, and introduction to fighter fundamentals training.

Function: Trainer.

Operator: ACC, AETC, AFMC, AFRC.

First Flight: April 1959.

Delivered: 1961-72.

IOC: March 1961.

Production: more than 1,100.

Inventory: 459.

Unit Location: Active: Beale AFB and Edwards AFB, Calif., Columbus AFB, Miss., Holloman AFB, N.M., Laughlin AFB, Randolph AFB, and Sheppard AFB, Tex., Vance AFB, Okla., Whiteman AFB, Mo. AFRC: Randolph AFB, Tex. (assoc.).

Contractor: Northrop Grumman.

Power Plant: two General Electric J85-GE-5A turbojets, each 2,680 lb thrust dry, 2,900 lb thrust with afterburning.

Accommodation: two, in tandem, on ejection seats.

Dimensions: span 25.3 ft, length 46.3 ft, height 12.8 ft.

Weight: empty 7,164 lb, gross 12,500 lb.

Ceiling: above 55,000 ft.

Performance: max level speed 812 mph, range 1,000 miles.

COMMENTARY

Most of the T-38s in service are used by AETC for advanced bomber-fighter training track in JSUPT and IFFT. Capabilities are being enhanced through an ongoing program of modifications and structural renewal, including a full avionics upgrade with a HUD and integrated GPS/INS, and a propulsion modernization. As a result of the reduction in the T-38's workload through introduction of the T-1A and JSUPT, the service life of the T-38s should extend well beyond 2020.

T-38A. Close in structure to the F-5A export tactical fighter, the T-38A was the world's first supersonic trainer aircraft. It is used to teach supersonic techniques, aerobatics, formation, night and instrument flying, and cross-country and low-level navigation. The aircraft is also used by AFMC to train test pilots and flight-test engineers at Edwards AFB, Calif., in experimental techniques, and by ACC as a companion trainer to maintain pilot proficiency.

AT-38B. A slightly different version, with a gunsight and



T-38 Talon (SrA. Matthew C. Simpson)

practice bomb dispenser, the AT-38B is used by AFMC for test and evaluation.

T-38C. C model T-38s are rewinged A and B airframes with modifications of the avionics systems to include a HUD. The first T-38C was delivered late summer 2002; last delivery was made in summer 2007. The propulsion system is also being upgraded to improve performance and reliability. In addition, the Escape System Upgrade Program is under way to further improve safety and sustainability of the aircraft and improve aircrew accommodation.

T-41 Mescalero

Brief: Short-range, high-wing trainer used primarily for aerodynamic and navigation courses.

Function: Training, support.

Operator: AETC.

Delivered: 1969.

Inventory: four.

Unit Location: USAFA, Colo.

Contractor: Cessna.

Power Plant: one Continental IO-360-DB piston engine, 210 hp.

Accommodation: two, side by side.

Dimensions: span 36.1 ft, length 26.5 ft, height 8.9 ft.

Weight: gross 2,550 lb.

Ceiling: 16,000 ft.

Performance: speed 182 mph, range 690 miles.

COMMENTARY

The **T-41D**, a military version of the Cessna 172, is an all-metal, strut-braced high-wing monoplane. The aircraft is equipped with modern avionics, GPS, and other equipment appropriate to its mission. It is used for Aero 456 flight testing, USAFA flying team support, and orientation flights.

T-43

Brief: A medium-range, swept-wing jet aircraft equipped with navigation and communications equipment to train navigators for strategic and tactical aircraft.

Function: Navigation trainer.

Operator: AETC.

First Flight: April 1973.

Delivered: September 1973-July 1974.

IOC: 1974.

Production: 19.

Inventory: eight.

Unit Location: Randolph AFB, Tex.

Contractor: Boeing.

Power Plant: two Pratt & Whitney JT8D-9 turbofans, each 14,500 lb thrust.

Accommodation: crew of two; 12 students and six instructors.

Dimensions: span 93 ft, length 100 ft, height 37 ft.

Weight: gross 115,500 lb.

Ceiling: 37,000 ft.

Performance: econ cruising speed 535 mph (Mach 0.7), operational range 2,995 miles.

COMMENTARY

T-43A. The T-43A was derived from the commercial Boeing Model 737-200 and was equipped with the same onboard avionics as most USAF operational aircraft, including mapping radar, VHF omnidirectional radio and Tacan radio systems, INS, radar altimeter, all required communications equipment, and celestial navigation capability. A number of T-43s are configured for passengers and provide operational support to assigned commands.

T-51

Brief: A light aircraft used by USAFA flying team for training and competition.

Function: Training, competition.

Operator: AETC.

Inventory: three.

Unit Location: USAFA, Colo.

Contractor: Cessna.

Power Plant: one Lycoming O-320 E2D piston engine, 150 hp.

Accommodation: two, side by side.

Dimensions: span 33.3 ft, length 24.8 ft, height 8.5 ft.

Weight: (Cessna 150M) gross 1,600 lb.

Ceiling: 14,000 ft plus.

Performance: speed 124 mph, range 475 miles.

COMMENTARY

The T-51 is a military version of the Cessna 150 used by students at USAFA for training and competition.

TG-10B Merlin

Brief: Two-seat medium-performance sailplane used for introductory glider training, instructor upgrade training, spin training, and basic cross-country soaring training.

Function: Trainer.

Operator: AETC.

Delivered: May 2002.

IOC: December 2002.

Inventory: 12.

Unit Location: USAFA, Colo.

Contractor: Blanik.

Accommodation: two.

Dimensions: span 55.4 ft, length 27.9 ft, height 6.2 ft.

Weight: 1,168 lb.

Performance: speed 142.6 mph, glide ratio 28:1.

COMMENTARY

The **TG-10B** is an L-23 Super Blanik dual sailplane, produced in the Czech Republic and used by USAFA to introduce cadets to flight through the Basic Soaring program.

TG-10C Kestrel

Brief: Two-seat medium-performance sailplane used for spin and aerobatic training.

Function: Trainer.

Operator: AETC.

Delivered: May 2002.

IOC: December 2002.

Inventory: five.

Unit Location: USAFA, Colo.

Contractor: Blanik.

Accommodation: two.

Dimensions: span 46.6 ft, length 27.6 ft, height 6.9 ft.

Weight: 1,100 lb.

Performance: speed 146.1 mph, glide ratio 26:1.

COMMENTARY

The **TG-10C** is an L-13AC Blanik dual sailplane, produced in the Czech Republic and used primarily for spin and aerobatic training.

TG-10D Peregrine

Brief: Single-seat medium-performance sailplane used for cross-country soaring training and high-altitude wave flight.

Function: Trainer.

Operator: AETC.

Delivered: May 2002.

IOC: December 2002.

Inventory: four.

Unit Location: USAFA, Colo.

Contractor: Blanik.

Accommodation: single.

Dimensions: span 46.3 ft, length 21.7 ft, height 4.7 ft.

Weight: 750 lb.

Performance: speed 149.5 mph, glide ratio 33:1.

COMMENTARY

The **TG-10D** is an L-33 Solo Blanik sailplane produced in the Czech Republic. It is a medium-performance sailplane that allows students to master basic flight maneuvers while solo, before progressing to a more advanced sailplane. It is primarily used for cross-country training and high-altitude wave flight.

TG-14A

Brief: A two-place, side-by-side motorized glider for use by USAFA in its Introductory Flight Training Program (IFTP) flight screening/primary training program.

Function: Trainer.

Operator: AETC.

Delivered: September 2002.

IOC: December 2002.

Inventory: four.

Unit Location: USAFA, Colo.

Contractor: Grupo Aeromot, Brazil.

Power Plant: one Rotax 912A, 81 hp engine.

Accommodation: two, side by side.

Dimensions: span 57.3 ft, length 26.4 ft, height 6.3 ft.

Weight: gross 1,874 lb.

Performance: cruise speed 110 mph, glide ratio 31:1, range 690 miles at high-speed cruise, max endurance seven hr.

COMMENTARY

The **TG-14A** is a version of the Ximango AMT-200S Sport Grupo Aeromot selected for use at USAFA in IFTP, replacing the Enhanced Flight Screening Program performed by civilian flying schools since the grounding of the T-3A Firefly in 1997. Cockpit and avionics are arranged for military use. Students use it to practice multiple pattern, aerial maneuvers, and landing procedures, reducing by half the number of sorties needed to achieve a solo flight.

TG-15A

Brief: A two-seat high-performance advanced training/cross-country sailplane for use by USAFA cadets in support of glider competition events nationwide.

Function: Trainer/cross-country competition sailplane.

Operator: AETC.

Unit Location: USAFA, Colo.

Inventory: two.

Contractor: Schempp-Hirth, Germany.

Accommodation: two-seat.

Dimensions: span 65.6 ft, length 28.3 ft.

Weight: gross 1,543 lb.

Performance: max permitted speed 155 mph, aspect ratio 24:4.

COMMENTARY

The **TG15A** is a high-performance advanced training/cross-country sailplane manufactured by Schempp-Hirth of Germany under the civilian designation Duo Discus. This world-class competition glider is dual seated and is intended for use nationwide by USAFA cadets for glider competition events.

TG-15B

Brief: A single-seat high-performance advanced training/cross-country sailplane for use by USAFA cadets for glider competition events nationwide.

Function: Trainer/cross-country competition sailplane.

Operator: AETC.

Unit Location: USAFA, Colo.

Inventory: three.

Contractor: Schempp-Hirth, Germany.

Accommodation: single seat.

Dimensions: span 49.2 ft, length 32.3 ft.

Weight: gross 1,157 lb.

Performance: max permitted speed 155 mph, aspect ratio 22:2.

COMMENTARY

The **TG15B** is a high-performance advanced training/cross-country sailplane manufactured by Schempp-Hirth of Germany under the civilian designation Discus 2b. This world-class competition glider is single seated and is intended for use nationwide by USAFA cadets for glider competition events.

UV-18 Twin Otter

Brief: Modified utility transport used for parachute jump training.

Function: Paratroop.



T-43A (Clive Bennett)

Operator: AETC.

First Flight: May 1965 (commercial version).

Delivered: 1977.

IOC: 1977.

Production: three.

Inventory: three.

Unit Location: USAFA, Colo.

Contractor: de Havilland Aircraft of Canada.

Power Plant: two Pratt & Whitney Canada PT6A-27 turboprops, each 620 ehp.

Accommodation: crew of two and up to 20 passengers.

Dimensions: span 65 ft, length 51.8 ft, height 19.5 ft.

Weight: gross 12,500 lb.

Ceiling: 26,700 ft.

Performance: max cruising speed 210 mph, range with 2,500 lb payload 806 miles.

COMMENTARY

The **UV-18B** is a military version of the DHC-6 Twin Otter STOL utility transport used for parachute jump training at USAFA.

Helicopters

HH-60G Pave Hawk

Brief: Specially modified helicopters used primarily for combat search and rescue, also aeromedical evacuation, civil SAR, and other support missions.

Function: CSAR medium-lift helicopter.

Operator: ACC, AETC, AFMC, PACAF, USAF, ANG, AFRC.

First Flight: October 1974.

Delivered: from 1982.

IOC: circa 1982.

Production: 105.

Inventory: 101.

Unit Location: Davis-Monthan AFB, Ariz., Kadena AB, Japan, Kirtland AFB, N.M., Moody AFB, Ga., Nellis AFB, Nev., RAF Lakenheath, UK. ANG: Francis S. Gabreski Arpt., N.Y., Kulis ANGB, Alaska, Moffett Field, Calif. AFRC: Davis-Monthan AFB, Ariz., Patrick AFB, Fla.

Contractor: Sikorsky.

Power Plant: two General Electric T700-GE-700/701C turboshafts, each 1,560-1,940 shp.

Accommodation: crew of six; 8-12 troops, two litters, or internal or external cargo.

Dimensions: rotor diameter 53.6 ft, length of fuselage 64.7 ft, height 16.7 ft.

Weight: max gross 22,000 lb.

Ceiling: 14,200 ft.

Performance: max speed 173 mph, max range 373 miles (internal fuel), 500 miles (auxiliary tank).

Armament: mounts for two 7.62 mm miniguns or two .50-caliber machine guns in cabin doors.

COMMENTARY

Black Hawk helicopters were modified to **HH-60G** Pave Hawk configuration in the early 1980s. Since that time, they have been in continuous use by active duty, ANG, and AFRC air rescue units for CSAR, humanitarian, and medevac mission activities worldwide. The Pave Hawk is a highly modified version of the Army Black Hawk helicopter, featuring an upgraded communications/navigation suite that includes INS/GPS/Doppler navigation systems, satellite communications (SATCOM), secure/anti-jam

communications, and a PLS that provides range/steering data to compatible survivor radios.

Additional modifications include an automatic flight-control system, NVG lighting, FLIR, color weather radar, engine/rotor blade anti-ice system, retractable in-flight refueling probe, internal auxiliary fuel tanks, and an integral rescue hoist. Combat enhancements include RWR, IR jammer, flare and chaff countermeasures dispensing system, and two 7.62 mm or .50-caliber machine guns.

MH-53 Pave Low

Brief: Specially outfitted heavy-lift helicopters used by Air Force special operations forces for infiltration/exfiltration as well as CSAR missions.

Function: SOF heavy-lift helicopter.

Operator: AFSOC.

First Flight: March 1967.

Delivered: from July 1987 (MH-53J).

IOC: 1988 (MH-53J).

Production: not available.

Inventory: 10 (MH-53M).

Unit Location: Hurlburt Field, Fla.

Contractor: Sikorsky; Texas Instruments.

Power Plant: two General Electric T64-GE-100 turboshafts, each 4,330 shp.

Accommodation: crew of six; up to 38 troops.

Dimensions: rotor diameter 72.2 ft, length of fuselage (without refueling probe) 67.2 ft, height 25 ft.

Weight: gross 50,000 lb.

Ceiling: 16,000 ft.

Performance: speed 164 mph, max range 630 miles, unlimited with air refueling.

Armament: mounts for any combination of three 7.62 miniguns and .50-caliber machine guns.

COMMENTARY

MH-53H. Older version of the helicopter, all of which, together with all HH/CH-53B/Cs, were upgraded to MH-53J Pave Low III "Enhanced" standard from 1986.

MH-53J. A long-range deep penetration helicopter, adverse weather capable and equipped for extended operations when air refueled. Equipped with a nose-mounted FLIR, an integrated digital avionics suite that includes TF/TA radar, Kalman filtered navigation suite (GPS, INS, Doppler), projected map display, secure UHF, VHF, FM, HF communications, PLS, SATCOM, hover coupler, rescue hoist, mission commander's C2 panel, armor plating, and an ECM suite with radar and IR missile jammers, flare/chaff dispensers, RWR, and missile launch detectors.

A service life extension program (SLEP) upgraded the aircraft's hydraulics, wiring, and basic airframe structure for increased gross weight, and an automated blade/pylon fold system optimized for shipboard compatibility. All aircraft modified to support aircrew eye/respiratory protection system.

MH-53M. MH-53J helicopters upgraded to Pave Low IV standard, delivered from 1999. Upgrades include the interactive defensive avionics suite/multimission advanced tactical terminal capability which integrates onboard EW systems with off-board, over-the-horizon, near-real-time intelligence, and mission software improvements. Cockpit modifications include three MFDs, integrated digital map, and mission commander situation awareness panel in the cabin area.

USAF had 10 aircraft still in TAI as of Sept. 30, 2008 and permanently retired them shortly thereafter.

UH-1

Brief: Modified Bell helicopter used to support Air Force ICBM facilities, undergraduate pilot training, aviation advisory aircrew flight proficiency, and administrative airlift.

Function: Utility and training helicopter.

Operator: AETC, AFMC, AFSOC, AFSPC, AMC, PACAF.

First Flight: 1956.

Delivered: from September 1970.

IOC: circa 1970.

Production: 79 (USAF).

Inventory: 21 (UH-1H); 62 (UH-1N).

Unit Location: Andrews AFB, Md., Fairchild AFB, Wash., F. E. Warren AFB, Wyo., Ft. Rucker, Ala., Hurlburt Field, Fla., Kirtland AFB, N.M., Malmstrom AFB, Mont., Minot AFB, N.D., Robins AFB, Ga., Yokota AB, Japan.

Contractor: Bell.

Power Plant: UH-1H: one Lycoming T53-L-13B turbo-shaft, 1,400 shp. UH-1N: Pratt & Whitney Canada T400-CP-400 Turbo "Twin-Pac," 1,290 shp.

Accommodation: two pilots and 14 passengers or cargo, or external load of 4,000 lb.

Dimensions: UH-1H: rotor diameter 48.3 ft, fuselage length 57.1 ft, height 13 ft. UH-1N: rotor diameter (with tracking tips) 48.1 ft, fuselage length 42.3 ft, height 14.3 ft.

Weight: UH-1H: gross 9,500 lb. UH-1N: gross 11,200 lb.

Ceiling: UH-1H: 15,000 ft. UH-1N: 13,000 ft.

Performance: max cruising speed at S/L 115 mph, max range, no reserves, 261 miles.

Armament: (optional) two General Electric 7.62 mm miniguns or two 40 mm grenade launchers; two seven-tube 2.75-in rocket launchers.

COMMENTARY

UH-1H is a former Army-owned training helicopter transferred to USAF in 2004 for use by the 23rd Flying Training Squadron at Ft. Rucker, Ala., for Air Force undergraduate helicopter pilot training. It is a single-engine version of the UH-1 utility helicopter (Bell Model 205) equipped with a rescue hoist. Two UH-1H helicopters are maintained by AFSOC for aviation advisory aircrew flight proficiency.

UH-1N is a twin-engine version of the UH-1 utility helicopter (Bell Model 212), most of which are allocated for AFSPC missile security and for administrative/DV airlift. The UH-1N is also used by AETC's 58th SOW, Kirtland AFB, N.M., for training purposes and by the 336th TRG, Fairchild AFB, Wash., for aircrew survival training. Two UH-1N helicopters are maintained by AFSOC for aviation advisory aircrew flight proficiency.

TH-1H is a modified version of the UH-1H for use in undergraduate helicopter pilot training. The TH-1H is a "zero-time" aircraft that includes upgraded power train components and a "glass" cockpit. USAF planned to acquire 24, beginning in October 2008.

Strategic Missiles

AGM-86 Air Launched Cruise Missile

Brief: A small, subsonic, winged air vehicle, deployed on B-52H aircraft, which can be equipped with either a nuclear or conventional warhead and can be used to help destroy/defeat air defenses and complicate an enemy's air defense task.

Function: Strategic air-to-surface cruise missile.

Operator: ACC.

First Flight: June 1979 (full-scale development).

Delivered: from 1981.

IOC: December 1982, Griffiss AFB, N.Y.

Production: 1,700+.

Unit Location: Barksdale AFB, La., Minot AFB, N.D.

Contractor: Boeing.

Power Plant: Williams/Teledyne CAE F107-WR-10 turbofan, 600 lb thrust.

Guidance: AGM-86B: inertial plus Terrain Contour Matching (TERCOM); AGM-86C: inertial plus GPS.

Warhead: AGM-86B: W80-1 nuclear; AGM-86C: blast/fragmentation conventional; AGM-86D: hard target penetrating warhead.

Dimensions: length 20.8 ft, body diameter 2 ft, wing-span 12 ft.

Weight: 3,150 lb (B), 3,277 lb (C).

Performance (approx): speed 550 mph (Mach 0.6), range 1,500+ miles (AGM-86B).

COMMENTARY

AGM-86A. A prototype cruise missile, developed in the mid-1970s. Slightly smaller than the later versions, it never entered production.

AGM-86B. First production version, the B is programmed for strategic attack on surface targets. Small radar signature and low-level flight capability enhance the missile's effectiveness. The last of 1,715 production models was delivered in October 1986. A SLEP has been ongoing to extend service life to 2030; however, in 2007 USAF announced its intention to reduce the ALCM fleet by more than 500 missiles, leaving 528 nuclear cruise missiles. The ALCM force is to be consolidated at Minot AFB, N.D.,



HH-60G Pave Hawk (SSgt. Aaron Allmon)

and all excess cruise missile bodies destroyed.

AGM-86C. A conventional warhead version, developed from June 1986, the Conventional Air Launched Cruise Missile (CALCM) was first used operationally during Gulf War I and has since been used widely in combat operations. CALCM provides an adverse weather, day/night, air-to-surface, accurate, standoff, outside theater defenses strike capability, with a range greater than 500 miles and a 3,000-lb class warhead. CALCM has proved equally effective for stand-alone, clandestine/punitive strikes and fully integrated theater warfare. From 1986, Boeing converted 622 Bs to the conventional configuration, the first of which was delivered in December 1987. The remaining CALCMs feature Block 1A enhancements with improved accuracy and increased immunity to electronic jamming. Since Iraqi Freedom, few CALCMs remain.

AGM-86D. CALCM Block II penetrator version with a Lockheed Martin AUP-3(M) warhead. The CALCM penetrator provides a standoff, outside theater defenses capability against a wide range of hardened, deeply buried targets. The CALCM penetrator was used with success in Iraqi Freedom.

AGM-129 Advanced Cruise Missile

Brief: A stealthy, long-range, winged air vehicle equipped with a nuclear warhead and designed to evade enemy air- and ground-based defenses in order to strike hard, heavily defended targets at standoff distances.

Function: Strategic air-to-surface cruise missile.

Operator: ACC.

First Flight: July 1985.

Delivered: June 1990-August 1993.

IOC: circa 1991.

Production: 461.

Unit Location: Barksdale AFB, La., Minot AFB, N.D.

Contractor: General Dynamics (now Raytheon); McDonnell Douglas (now Boeing).

Power Plant: Williams International F112-WR-100 turbofan.

Guidance: inertial, with TERCOM update.

Warhead: W80-1 nuclear.

Dimensions: length 20.8 ft, body width 2.2 ft, wingspan 10.2 ft.

Weight: 3,700 lb.

Performance (approx): range 2,300+ miles, speed 550 mph.

COMMENTARY

AGM-129A. Embodying stealth technology, the AGM-129A is an air-launched strategic cruise missile, carried externally on B-52H aircraft, with significant improvements over the AGM-86B in range, accuracy, and survivability. Despite modification to extend its service life to 2030, USAF now plans to retire its entire ACM inventory.

LGM-30 Minuteman

Brief: A solid-fuel ICBM capable of being fired from silo launchers and delivering a thermonuclear payload of one to three warheads with high accuracy over great distances.

Function: Strategic air-to-surface ballistic missile.

Operator: AFSPC.

First Flight: February 1961.

Delivered: 1962-December 1978.

IOC: December 1962, Malmstrom AFB, Mont.

Production: 1,800.

Unit Location: F. E. Warren AFB, Wyo., Malmstrom AFB, Mont., Minot AFB, N.D.

Contractor: Boeing.

Power Plant: stage 1: Thiokol M-55 solid-propellant motor, 210,000 lb thrust; stage 2: Aerojet General SR19-AJ-1 solid-propellant motor, 60,300 lb thrust; stage 3: Thiokol SR73-AJ-1 solid-propellant motor, 34,400 lb thrust.

Guidance: inertial guidance system.

Warheads: one-three Mk 12/12A MIRVs (downloaded to one).

Dimensions: length 59.8 ft, diameter of first stage 5.5 ft.

Weight: launch weight (approx) 78,000 lb.

Performance: speed at burnout more than 15,000 mph, highest point of trajectory approx 700 miles, range with max operational load more than 6,000 miles.

COMMENTARY

A key element in the US strategic deterrent posture, Minuteman is a three-stage, solid-propellant ICBM, housed in an underground silo.

LGM-30A/B. Minuteman I version deployed in the early 1960s. The last Minuteman I missile was removed from its silo at Malmstrom AFB, Mont., in February 1969. USAF had deployed 150 A and 650 B models in 16 squadrons.

LGM-30F. Minuteman II version incorporated a larger second stage, an improved guidance package, greater range and payload capability, and hardening against the effects of nuclear blast. IOC was reached in October 1965 at Grand Forks AFB, N.D. USAF deployed 450 in nine squadrons.

LGM-30G. The Minuteman III became operational in June 1970, providing improved range, rapid retargeting, and the capability to place three MIRVs on three targets with a high degree of accuracy. USAF initially deployed 550 in 11 squadrons, later reducing to 500 based at F. E.



LGM-30 Minuteman III (USAF photo)

Warren, Malmstrom, and Minot. Deactivation of a further 50 Minuteman IIIs was completed in July 2008 at Malmstrom. Components of the dismantled missiles are to be used for flight-test operations programs.

In accordance with strategic arms control negotiations, all the three-warhead Minuteman III missiles at F. E. Warren have been downloaded to single re-entry vehicles.

An extensive life extension program is ensuring Minuteman III's viability to 2020. Major upgrades include refurbishment of liquid propulsion post-boost rocket engine, remanufacture of the solid-propellant rocket motors, replacement of the environmental control system, repair of launch facilities, installation of updated, survivable communications equipment, and a C2 sustainment program. Further proposed incremental upgrades from 2020 are intended to maintain the ICBMs' viability to 2040 and beyond.

Tactical Missiles and Weapons

AGM-65 Maverick

Brief: A tactical, TV- or imaging infrared (IIR)-guided air-to-surface missile carried by fighters and designed for use in CAS, interdiction, and defense suppression missions, having standoff capability and high probability of strike against a wide range of targets.

Function: Air-to-surface guided missile.

First Flight: August 1969.

Delivered: from August 1972.

IOC: February 1973.

Production: sustainment phase.

Contractor: Raytheon.

Power Plant: Thiokol TX-481 solid-propellant rocket motor.

Guidance: self-homing, EO guidance system (IIR on D and G models).

Warhead: AGM-65A/B/D/H 125-lb high-explosive, shaped charge; AGM-65G/K 298-lb blast fragmentation.

Dimensions: length 8.2 ft, body diameter 1 ft, wingspan 2.3 ft.

Weight: launch weight (AGM-65A) 462 lb, (AGM-65G) 670 lb.

Performance: range about 9.2 miles.

COMMENTARY

Maverick missiles have a long and distinguished combat record. They were first employed by USAF in Vietnam and were used extensively during Gulf War I and II. The weapon is integrated with A-10, F-15E, and F-16 aircraft for use against tanks and columns of vehicles and in the SEAD role.

AGM-65A. The basic Maverick is a launch-and-leave, TV-guided air-to-surface missile that enables the pilot of

the launch aircraft to seek other targets or leave the target area once the missile has been launched. Production was initiated in 1971, following successful test launches over distances ranging from a few thousand feet to many miles and from high altitudes to treetop level.

AGM-65B. A version with a "scene magnification" TV seeker that enables the pilot to identify and lock on to smaller or more distant targets.

AGM-65D. System developed to overcome limitations of the TV Maverick, which can be used only in daylight and clear-weather conditions. This version has an IIR seeker as well as a lower-smoke motor. IIR Maverick became operational in February 1986 on A-10 aircraft.

AGM-65E. A laser guided version ordered by USN and USMC. To meet short-term operational requirements, USAF has used missiles from the Navy's inventory in combat operations, beginning June 2007. A new production state-of-the-art version of the laser guided Maverick for the Navy and Air Force is anticipated for 2009.

AGM-65G. Uses the IIR seeker with an alternate 298-lb blast fragmentation warhead for use against hardened targets. Software is modified to include options for targeting ships and large land targets as well as mobile armor. This version also has a digital autopilot and a pneumatic, rather than hydraulic, actuation system. USAF received its first G model in 1989.

AGM-65H. AGM-65B modified with an upgraded TV seeker providing significant reliability, maintainability, and performance improvements over the AGM-65B seeker and double the standoff range.

AGM-65K. AGM-65G modified with the same upgraded TV seeker as in the AGM-65H to provide a TV-guided version of the Maverick with the 298-lb blast fragmentation warhead.

A new, low-collateral-damage variant of the AGM-65H/K, with an improved and newly manufactured laser seeker, is being acquired for precision strike against high-speed, fleeting targets in urban areas. Initial buy is expected 2010.

AGM-88 HARM

Brief: An air-to-surface tactical missile designed to seek and destroy enemy radar-equipped air defense sites, using an advanced guidance system that senses and homes in on enemy radar emissions.

Function: Air-to-surface anti-radiation missile.

First Flight: April 1979.

Delivered: 1982-98.

IOC: circa 1984.

Production: sustainment phase.

Contractor: Raytheon.

Power Plant: Thiokol smokeless, dual-thrust, solid-propellant rocket motor.

Guidance: passive homing guidance system, using seeker head that homes on enemy radar emissions.

Warhead: high-explosive fragmentation, weighing 145 lb.

Dimensions: length 13.7 ft, body diameter 10 in, wingspan 3.7 ft.

Weight: 795 lb.

Performance: cruising speed supersonic, altitude limits S/L to 40,000 ft, range more than 10 miles.

COMMENTARY

A joint USAF-USN project, the High-speed Anti-Radiation Missile (HARM) exhibits great velocity along with an ability to cover a wide range of frequency spectrums through the use of programmable digital processors in both the carrier aircraft's avionics equipment and in the missile. The combination gives this second generation anti-radiation missile (ARM) greatly improved capability over first generation Shrikes and Standard ARMs. The AGM-88 proved highly effective against enemy ground radar in Gulf War I and in subsequent operations. HARMs equip F-16 Block 50/52s (F-16CJ) dedicated to the SEAD mission.

AGM-88A. A factory-programmed version used to equip the now-retired F-4G Wild Weasel to increase its lethality in electronic combat. No longer operational.

AGM-88B. Incorporated erasable electronically programmable read-only memory, permitting changes to missile memory in the field. Older versions of the AGM-88B have software upgrades to satisfy current-standard capability requirements.

AGM-88C. This current version has a more lethal warhead, containing tungsten alloy cubes, rather than steel, and the enhanced-capability AGM-88C-1 guidance head.

Upgrade initiatives have been aimed at increasing capability of both B and C versions against target shutdown, blinking, and blinking, and at reducing potential damage to friendly radars in the target area. In addition GPS precision navigation capability has been demonstrated through a modification of the control section known as the HARM Destruction of Enemy Air Defenses (DEAD) Attack Module, or HDAM.

AGM-154 Joint Standoff Weapon

Brief: Joint USAF and Navy family of low-cost glide weapons with a standoff capability.

Function: Air-to-surface guided missile.

First Flight: December 1994.

Delivered: from 2000.



AGM-88 HARM (DOD photo)

IOC: 2000 (USAF).
Production: 6,114 (originally planned).
Contractor: Raytheon.
Guidance: INS/GPS.
Dimensions: length 13.3 ft.
Weight: 1,065-1,500 lb.
Performance: range: low-altitude launch 17 miles, high-altitude launch 40+ miles.

COMMENTARY

A medium-range, INS/GPS-guided, standoff air-to-ground weapon designed to attack a variety of soft and armored area targets (fixed, relocatable, and mobile) during day/night/adverse weather conditions. JSOW enhances aircraft survivability by providing the capability for launch aircraft to stand off outside the range of enemy point defenses. JSOW accuracy and launch-and-leave capability allow several target kills per aircraft sortie. JSOW arms B-2 and F-16 aircraft. Production for USAF terminated FY05.

AGM-154A. The baseline BLU-97 variant for use against area targets.

AGM-154B. The BLU-108 variant provides anti-armor capability; development complete, production deferred.

AGM-154C. The third variant (used by Navy only), JSOW/Unitary integrates an IIR terminal seeker and a 500-lb unitary warhead.

AGM-158A Joint Air-to-Surface Standoff Missile

Brief: An advanced weapon designed to attack heavily defended targets with high precision at great standoff range.

Function: Air-to-surface guided weapon.

First Flight: April 8, 1999.

Delivered: through FY19 (planned).

IOC: September 2003. JASSM-ER projected 2010.

Production: 2,400, plus 2,500 JASSM-ER (planned).

Contractor: Lockheed Martin; Raytheon; Honeywell.

Guidance: INS, GPS, and IIR terminal seeker.

Power Plant: Teledyne Continental Motors.

Dimensions: length 14 ft.

Weight: 2,250 lb.

Performance: 1,000-lb class penetrator and blast-fragmentation warheads; standoff range greater than 200 miles.

COMMENTARY

JASSM is a next generation missile that enables Air Force fighters and bombers to destroy the enemy's war-sustaining capabilities from outside the ranges of enemy air defenses. This autonomous precision strike weapon has a range greater than 200 miles and can attack both fixed and relocatable targets, ranging from nonhardened above ground to moderately hardened buried targets. JASSM is equipped with INS/GPS guidance, an IIR terminal seeker, and a stealthy LO airframe. The system also offers low operational support costs. IOC has been declared on the B-1B, B-2, B52H, and F-16. Integration on F-15E and F-35 aircraft is proceeding. The B-1B is the only aircraft capable of redirecting a JASSM route prior to launch. Delivery of an extended-range version (**JASSM-ER**), with a range of more than 500 miles, is expected to begin in 2010.

AIM-7 Sparrow

Brief: A supersonic, medium-range, semiactive radar-guided air-to-air missile with all-weather, all-altitude, and all-aspect offensive capability and a high-explosive warhead, carried by fighter aircraft.

Function: Air-to-air guided missile.

First Flight: December 1983 (AIM-7M).

Delivered: from 1956.

IOC: April 1976 (AIM-7F).

Production: sustainment phase.

Contractor: Hughes; General Dynamics (now Raytheon).

Power Plant: Hercules Mk 58 Mod 0 4.5 sec boost 11 sec sustain rocket motor.

Guidance: AIM-7M: monopulse semiactive radar.

Warhead: high-explosive, blast fragmentation, weighing 86 lb.

Dimensions: length 12 ft, body diameter 8 in, wing-span 3.3 ft.

Weight: launch weight 504 lb.

Performance (estimated): max speed more than 2,660 mph (Mach 3.5), range more than 34 miles.

COMMENTARY

Early versions. Production of Sparrow has been under way for nearly half a century. Approximately 34,000 early models (AIM-7A/B/C/D/E) were produced. Compared to the earlier versions, the advanced solid-state AIM-7F, introduced into USAF service in 1976, had a larger motor, Doppler guidance, improved ECM, and better capability over both medium and "dogfight" ranges. USAF produced approximately 5,000, but none are now in USAF service.

AIM-7M. A joint Navy-USAF project aimed at producing a monopulse version of Sparrow at reduced cost and with improved performance in the ECM and look-down clutter regions. It began operational service in FY83. This version provides all-weather, all-altitude, all-aspect capability and equips USAF F-15s and F-16s (ADF) and Navy F-18s.

AIM-7P. Block 1 retrofit to AIM-7M guidance and control sections (GCSs), providing low-altitude guidance and fuzing capability. Block 2 provides new-build for AIM-7P GCSs.

AIM-9 Sidewinder

Brief: A supersonic, short-range, IR-guided air-to-air

missile carried by fighter aircraft, having a high-explosive warhead.

Function: Air-to-air missile.

First Flight: September 1953.

Delivered: 1957-present. First production AIM-9X delivered May 1, 2002.

IOC: circa 1983 (AIM-9M).

Production: sustainment phase (AIM-9M); LRIP from November 2000, with full rate from November 2004 (AIM-9X).

Contractor: Raytheon; Loral.

Power Plant: Thiokol Mk 36 Mod 11 solid-propellant rocket motor.

Guidance: solid-state IR homing guidance.

Warhead: high-explosive, weighing 20.8 lb.

Dimensions: length 9.4 ft, body diameter 5 in, fin-span 2.1 ft.

Weight: launch weight 190 lb.

Performance: max speed Mach 2+, range 10+ miles.

COMMENTARY

Early versions. AIM-9A was the prototype version. The AIM-9B, initial production version, entered the inventory in 1957 and was effective only at close range during day. These shortcomings were eliminated on subsequent AIM-9E/H/J/P versions. The third generation Sidewinder, AIM-9L, added a more powerful solid-propellant rocket motor as well as tracking maneuvering ability. Production and delivery began in 1976; production ended in 1981.

AIM-9M. A joint Navy-USAF project aimed at producing an improved version of AIM-9L with all-altitude, all-aspect, launch-and-leave intercept capability. Can equip: A-10, F-15, F-16, F-16 ADF, and F-18 aircraft. This version has increased infrared counter-countermeasures (IRCCM) capability, improved background discrimination, and a reduced-smoke rocket motor. First flight of prototype was in February 1978. Full production began in FY81.

AIM-9M-9. A modification to improve IRCCM capability of early missiles. Complete.

AIM-9X. Deriving from a jointly funded Navy-USAF project, the AIM-9X entered LRIP in November 2000. In November 2003, USAF's F-15-equipped 12th and 19th FS, part of the 3rd Wing at Elmendorf AFB, Alaska, were the first operational units to receive AIM-9Xs. Full-rate production was contracted in November 2004. USAF plans to buy 5,097 missiles.

The AIM-9X incorporates advanced technologies such as a focal plane array imaging seeker, high off-boresight sensor (HOBS), and a highly maneuverable jet-vane control system. The missile utilizes the existing AIM-9M rocket motor, warhead, and fuze. Carrier aircraft include the F-15, F-16, F-22, F-35, and F/A-18.

AIM-120 AMRAAM

Brief: A next generation supersonic, medium-range, active radar-guided air-to-air missile with a high-explosive warhead.

Function: Air-to-air guided missile.

First Flight: December 1984.

Delivered: 1988-July 2010 (planned).

IOC: September 1991.

Production: 10,917+ planned for USAF/USN.

Contractor: Raytheon.

Power Plant: Alliant boost-sustain solid-propellant rocket motor.

Guidance: inertial/command, inertial with active radar terminal homing.

Warhead: high-explosive directed fragmentation weighing 48 lb.

Dimensions: (A/B models) length 12 ft, body diameter 7 in, span of tail control fins 2.1 ft.



AIM-9 Sidewinder (TSgt. Jeffrey Allen)

Weight: 335 lb.

Performance: cruising speed approx Mach 4, range more than 23 miles.

COMMENTARY

A joint project between the Navy and USAF, the AIM-120 Advanced Medium-Range Air-to-Air Missile (AMRAAM) is a replacement for the AIM-7 Sparrow. The AIM-120 equips F-15, F-16, F-22, F-35, and F/A-18 fighters. Inertial and command inertial guidance and active radar terminal homing provide launch-and-maneuver capability. Significant improvements in operational effectiveness over the AIM-7 include increased average velocity, reduced miss distance, improved fuzing, increased warhead lethality, multiple target engagement capability, improved clutter rejection in low-altitude environments, enhanced electronic protection capability, increased maximum launch range, a reduced-smoke motor, and improved maintenance and handling.

AIM-120A was the first production version, delivered by Hughes in 1988 to the 33rd TFW at Eglin AFB, Fla.

AIM-120B/C/D are upgraded, reprogrammable variants of the AIM-120. The AIM-120C currently in production has smaller, clipped control surfaces to provide for internal carriage in the F-22A and F-35, and involves HOBBS launch capability. The latest development (AMRAAM Phase 4) adds an enhanced electronic protection suite, two-way data link, and GPS-aided navigation in the AIM-120D version. Production began 2006.

CBU-87/103 Combined Effects Munition

Brief: The CBU-87 CEM is an area munition effective against light armor, materiel, and personnel and used by USAF and Navy fighters and bombers for interdiction.

Function: Area munition.

Production: sustainment phase.

Contractor: Aerojet General; Honeywell; Alliant Tech.

Guidance: none (CBU-87).

Dimensions: length 7.7 ft; diameter 1.3 ft.

Weight: 949 lb.

Performance: dispenses 202 BLU-97 combined effects bomblets over an area roughly 800 ft by 400 ft.

COMMENTARY

The CBU-87 Combined Effects Munition dispenses BLU-97 shaped charge anti-personnel/anti-materiel fragmentary/incendiary bomblets over the target in a rectangular pattern. It is currently delivered by USAF and Navy aircraft as an unguided gravity weapon. Density and size of the area covered depends on release parameters and spin rates.

CBU-103. Unguided CBU-87 CEMs retrofitted with the Wind-Corrected Munitions Dispenser (WCMD) tail kit. The WCMD improves the munitions delivery accuracy when released from medium to high altitude.

CBU-89/104 Gator

Brief: The CBU-89 Gator is an anti-armor/anti-personnel mine dispenser used by USAF and Navy fighters and bombers for interdiction.

Function: Scatterable mines.

Production: sustainment phase.

Contractor: Honeywell; Aerojet General; Olan; Alliant Tech.

Guidance: none (CBU-89).

Dimensions: length 7.7 ft; diameter 1.3 ft.

Weight: 705 lb.

Performance: dispenses 72 BLU-91 anti-armor and 22 BLU-92 anti-personnel mines.

COMMENTARY

The CBU-89 Gator dispenser holds 94 mines, of which 72 are anti-tank and 22 are anti-personnel. The mines are dispersed over the target in a circular pattern. The anti-tank mines, which can be fuzed for three different time delay settings, have a magnetic influence fuze to sense armor.

CBU-104. Gators retrofitted with the WCMD tail kit, improving the munitions delivery accuracy when released from medium to high altitude.

CBU-97/105 Sensor Fuzed Weapon

Brief: The CBU-97 SFW is an anti-armor munition used by fighters and bombers for multiple kills per pass against moving and stationary land combat vehicles.

Function: Wide-area munition.

First Flight: circa 1990.

Delivered: 1994-2013 (planned).

IOC: 1997.

Production: 6,500 (planned).

Contractor: Textron Systems.

Guidance: IR sensors in each warhead search for targets, then detonate over them.

Dimensions: length 7.7 ft; diameter 1.3 ft.

Weight: 920 lb.

Performance: delivers 40 lethal projectiles over an area of about 500 ft by 1,200 ft.

COMMENTARY

The CBU-97 Sensor Fuzed Weapon (SFW) comprises an SUU-66/B tactical munitions dispenser with an FZU-39 fuze and a payload of 10 BLU-108 submunitions. Each tactical munitions dispenser contains 10 BLU-108 submunitions, and each submunition contains four "skeet" projectiles



GBU-10 Paveway II (DOD photo)

that, upon being thrown out, seek out their target and deliver an explosively formed penetrator. Each SFW can deliver a total of 40 lethal projectiles. The skeet's active laser and passive IR sensors can detect a vehicle's shape and IR signature; if no target is detected, the warhead detonates after a preset time. The SFW's primary targets are massed tanks, armored personnel carriers, and self-propelled targets. It also provides direct attack capability and interdiction against C2 centers.

The CBU-97 SFW is delivered as an unguided gravity weapon from the A-10, B-1, B-2, B-52H, F-15E, and F-16. The initial baseline SFW systems contained the BLU-108/B and BLU-108A/B submunition. A preplanned product improvement SFW submunition, the BLU-108B/B, incorporates improvements such as an active laser sensor, multimission warhead, and increased footprint and is the first area weapon to satisfy DOD's heightened deployment criteria for cluster weapons.

CBU-105. Designation of an unguided CBU-97 equipped with a Wind-Corrected Munitions Dispenser (WCMD) tail kit. The CBU-105 can be delivered accurately from high altitude and in adverse weather from the B-1, B-52H, F-15E, and F-16. Combat debut for the CBU-105 occurred April 2003, during Iraqi Freedom, from a B-52H.

CBU-107 Passive Attack Weapon

Brief: The CBU-107 Passive Attack Weapon (PAW) provides the capability to attack nonhardened surface targets, with a minimum of collateral and environmental damage.

Function: Wide-area munition.

First Flight: 2002.

Delivered: 2002-03.

IOC: December 2002.

Production: not available, but completed March 2003.

Contractor: General Dynamics (kinetic energy penetrator payload and canister); Lockheed Martin (WCMD); Textron (tactical munition dispenser kit).

Guidance: via WCMD.

Dimensions: length 7.7 ft; diameter 1.3 ft.

Weight: 1,000 lb.

Performance: delivers a high-speed volley of 3,000+ metal "arrows" projected from a single canister; three types of projectiles: 350 x 15 in-long rods, 1,000 x 7 in-long rods, and 2,400 small-nail size.

COMMENTARY

The CBU-107 Passive Attack Weapon (PAW) was developed from September 2002 to provide USAF aircraft with a new weapon that destroys targets with kinetic energy rods rather than explosives, thereby minimizing collateral and environmental damage. Following release from an aircraft, the WCMD-equipped weapon glides toward its target. Before impact, the inner chamber containing the rods begins to rotate and the "arrows" are ejected in rapid succession by centrifugal force, penetrating a target within a 200-ft radius. Two CBU-107s were used during Iraqi Freedom. CBU-107s are intended for use on B-52, F-15E, and F-16 aircraft.

GBU-10 Paveway II

Brief: An unpowered laser guided bomb (LGB) used to destroy high-value enemy targets from short standoff distances.

Function: Air-to-surface guided munition.

First Flight: early 1970s.

Delivered: from 1976.

IOC: 1976.

Production: 10,000; continuing.

Contractor: Lockheed Martin; Raytheon.

Guidance: semiactive laser.

Warhead: GBU-10C/D/E/F: Mk 84 bomb (2,000-lb unitary); GBU-10G/H/J: BLU-109.

Dimensions: length GBU-10C/D/E/F: 14.1 ft; GBU-10G/H/J: 14 ft; body diameter GBU-10C/D/E/F: 1.5 ft; GBU-10G/H/J: 1.2 ft, wingspan 5.5 ft.

Weight: 1,985 lb.

Performance: circular error probable (CEP) 29.7 ft; range 9.2 miles.

COMMENTARY

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The GBU-10 is used primarily for precision bombing against nonhardened targets but is capable of greater penetration than previous versions. It can operate in cloud ceilings down to 2,500 ft. GBU-10 platforms include A-10, B-52, F-15E, and F-16 aircraft.

GBU-12/49 Paveway II

Brief: An unpowered LGB used to destroy high-value enemy targets from short standoff distances.

Function: Air-to-surface guided munition.

First Flight: early 1970s.

IOC: 1976.

Production: about 30,000; continuing.

Contractor: Lockheed Martin; Raytheon.

Guidance: semiactive laser.

Warhead: Mk 82 (500 lb) blast/fragmentation bomb.

Dimensions: length 10.9 ft, body diameter 10.7 in, wingspan 4.4 ft.

Weight: 603 lb.

Performance: CEP 29.7 ft; range about 6 miles.

COMMENTARY

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The LGB is used primarily to strike fixed armor. It can operate in cloud ceilings down to 2,500 ft. GBU-12 platforms include A-10, B-52, F-15E, and F-16 aircraft.

The **GBU-49(V)B** (EGBU-12) variant features both laser guidance and on-board GPS for all-weather, precision delivery capability. Arming MQ-9 Reaper aircraft.

GBU-15

Brief: An unpowered bomb carried by the F-15E and used to destroy high-value enemy targets from short standoff distances.

Function: Air-to-surface guided munition.

First Flight: 1975.

Delivered: 1983-complete.

IOC: 1983.

Production: more than 2,000.

Contractor: Boeing; Raytheon.

Guidance: TV or IIR seeker.

Warhead: Mk 84 bomb (2,000-lb unitary) or BLU-109.

Dimensions: length 12.8 ft, body diameter 1.5 ft, wingspan 4.9 ft.

Weight: 2,500 lb.

Performance: cruising speed subsonic; range about 17 miles; CEP about 10 ft.

COMMENTARY

GBU-15 is an air-launched, cruciform-wing glide bomb fitted with a guidance system designed to give it pinpoint

accuracy from low or medium altitudes. It also has a standoff capability. Development began in 1974, based on experience gained in Vietnam with the earlier Pave Strike GBU-8 modular weapon program. The GBU-15 is intended for tactical use to suppress enemy defenses and to destroy heavily defended targets. The target-detecting device is carried on the front of the warhead. The control module, with autopilot and data link module, attaches to the rear.

The weapon has two modes of attack. In direct attack, the weapon is locked on to the target before launch and flies a near-line-of-sight profile to impact. In the indirect mode, the seeker can be locked on to the target after launch, or the operator can fly the weapon manually to impact, using guidance updates provided through the data link. A "buddy" system may be operated whereby the weapon is launched from one aircraft and controlled by another. The GBU-15 is deployed with the F-15E.

GBU-15(V)1/B. A TV-guided variant, qualified for operational service in 1983.

GBU-15(V)2/B. IIR version entered service in 1987.

GBU-15-I. Combines accuracy of GBU-15 with the penetration capability of the improved 2,000-lb BLU-109/B penetrator bomb.

EGBU-15. GPS-guided variant, allowing pilot to select either TV, IR, or GPS guidance over the target, depending on weather and/or threat conditions. Entered USAF service at the end of 1999. USAF initially produced 100 for Allied Force, in addition to the field-level upgrade of more than 1,200 existing GBU-15s.

GBU-16 Paveway II

Brief: An unpowered LGB used to destroy high-value enemy targets from short standoff distances.

Function: Air-to-surface glide munition.

First Flight: early 1970s.

IOC: 1976.

Production: not available.

Contractor: Lockheed Martin; Raytheon.

Guidance: semiactive laser.

Warhead: Mk 83 (1,000 lb) bomb.

Dimensions: length 12.1 ft, body diameter 1.2 ft, wingspan 5.5 ft.

Weight: approx 1,000 lb.

Performance: CEP about 29 ft; range 9.2 miles.

COMMENTARY

Folding-wing Paveway II weapons are improved versions of the earlier fixed-wing Paveway I. The GBU-16 LGB is used primarily to strike fixed armor. Its platforms include A-10, F-15E, and F-16 aircraft.

GBU-24 Paveway III

Brief: A precise air-to-ground low-level LGB (LLLGB) equipped with an advanced guidance kit.

Function: Air-to-surface penetrating glide bomb.

First Flight: GBU-24A/B (USAF) in service May 1985; GBU-24B (Navy) June 1992.

Delivered: from 1986.

IOC: 1986.

Production: 14,000 (USAF); 12,000 (USN).

Contractor: Raytheon.

Guidance: semiactive laser.

Warhead: BLU-109 (A/B); BLU-116 (C/D).

Dimensions: length 14.2 ft.

Weight: 2,350 lb.

Performance: range more than 11.5 miles.



GBU-24 Paveway III (USAF photo)

COMMENTARY

GBU-24A/B. An air-to-ground weapon equipped with the third generation Paveway III guidance kit, integrated with a BLU-109 penetrating warhead. The kit consists of an advanced guidance section and high-lift airframe. It is extremely precise and highly effective against a broad range of high-value hard targets. The system can be employed from low, medium, and high altitudes, providing operational flexibility through the use of an adaptive digital autopilot and large field-of-regard, highly sensitive scanning seeker. The GBU-24A/B was highly successful during Desert Storm.

GBU-24C/D. Variant integrated with the BLU-16 advanced unitary penetrator (AUP). The GBU-24 adapts to conditions of release, flies an appropriate midcourse, and provides trajectory shaping for enhanced warhead effectiveness. The weapon is deployed on USAF F-15E, and F-16 and Navy F/A-18 aircraft.

GBU-28

Brief: A large 5,000-lb class air-to-ground penetrating warhead (BLU-113/B) equipped with an advanced laser guidance kit, used for striking and destroying hard and deeply buried targets.

Function: Air-to-surface guided glide bomb.

First Flight: February 1991.

Delivered: circa 1991.

IOC: 1991.

Production: approx 500.

Contractor: Raytheon.

Guidance: laser.

Dimensions: length 19.2 ft, diameter 1.2 ft.

Weight: 4,676 lb.

Performance: range more than 5.75 miles.

COMMENTARY

Under USAF's rapid-response program, the GBU-28

bunker-busting LGB was developed for Desert Storm for use against deeply buried, hardened C2 facilities. Four of the GBU-28 weapons were used during the war: two for testing and two by F-111Fs against a bunker complex Feb. 27, 1991. Guidance is by a modified GBU-27 system.

GBU-28B/B. Integrates GPS/INS guidance into the existing GBU-28 guidance control unit to provide adverse weather capability and improved target location. Entered production in FY99.

GBU-28C/B. Utilizes the improved BLU-122/B warhead for increased penetration, lethality, and survivability. Guidance and control is provided by an Enhanced Paveway III system with GPS/INS and laser capability. Entered production in FY05.

GBU-31/32/38 Joint Direct Attack Munition

Brief: A joint USAF-Navy INS/GPS-guided weapon, carried by fighters and bombers, that provides highly accurate, autonomous, all-weather conventional bombing capability.

Function: Air-to-surface guided bomb.

First Flight: Oct. 22, 1996.

Delivered: 1998-2013 (planned).

IOC: 1998.

Production: 213,521 (planned).

Contractor: Boeing; Textron; Honeywell.

Guidance: INS/GPS.

Dimensions: Mk 84 with JDAM 12.8 ft; BLU-109 with JDAM 12.4 ft; Mk 83 with JDAM 10 ft; Mk 82 with JDAM 8 ft.

Weight: Mk 84 2,036/2,056 lb (USAF/USN); BLU-109 2,115/2,135 lb; Mk 83 1,013/1,028 lb; Mk 82 552/558 lb.

Performance: range up to 17 miles, CEP with GPS 16.4 ft; CEP with INS only 98 ft.

COMMENTARY

JDAM upgrades the existing inventory of general-purpose bombs by integrating them with a GPS/INS guidance kit to provide accurate all-weather attack from medium/high altitudes. While still aboard the launch aircraft, JDAM is passed target information through the aircraft's avionics system. Once released, the inertial guidance kit takes over and, with periodic GPS updates to the INS, guides the weapon to its target. JDAM is integrated on A-10, B-1, B-2, B-52, F-15E, F-16, F-22, and MQ-9 and AV-8B and F/A-18C/D/E/F aircraft, with future integration on F-35 aircraft.

GBU-31. Variant that adds an INS/GPS guidance kit to the 2,000-lb general-purpose Mk 84 bomb or the 2,000-lb BLU-109 penetrator. First used in combat March 24, 1999.

GBU-32. Variant that adds an INS/GPS guidance kit to the 1,000-lb general-purpose Mk 83 bomb or the 1,000-lb BLU-110 thermal coated bomb.

GBU-38. Variant that adds an INS/GPS guidance kit to the 500-lb general-purpose Mk 82 bomb or the 500-lb BLU-111 thermal coated bomb. First production deliveries were in 2004 for the B-2.

GBU-39B Small Diameter Bomb

Brief: Extended-range all-weather, day/night 250-lb class near-precision guided munition. Provides increased loadout to achieve multiple kills per sortie and decreases collateral damage.

Function: Air-to-surface guided munition.

First Flight: May 23, 2003 (guided).

Delivered: from 2006.

IOC: 2007.

Production: 24,000 munitions and 2,000 carriages (planned).

Contractor: Boeing (SDB I).



GBU-32 Joint Direct Attack Munition (MSgt. Michael Ammons)

Guidance: GPS/INS augmented by Differential GPS.
Dimensions: length 70.8 in (munition); 126.4 in (carriage); 143.1 in (carriage with four munitions).
Weight: 285 lb (munition); 320 lb (carriage); 1,460 lb (carriage with four munitions).
Performance: near-precision capability at standoff range up to 46 miles.

COMMENTARY

The Small Diameter Bomb (SDB) system employs a BRU-61/Asmart carriage capable of carrying four 250-lb class GBU-39/B near-precision guided air-to-surface munitions.

SDB I is capable of destroying high-priority fixed and stationary targets from both fighters and bombers in internal bays or on external hardpoints. SDBs can be targeted and released against single or multiple targets. Target coordinates are loaded in the weapon prior to release either on the ground or in the air by aircrew. Once the weapon is released, it relies on GPS/INS augmented by Differential GPS to self-navigate to the impact point. SDB increases loadout, decreases collateral damage, and improves aircraft sortie generation times. GBU-39 went operational in July 2006 on the F-15E. Objective aircraft include the A-10, B-1, B-2, B-52, F-16, F-22, F-35, and MQ-9. Boeing was awarded the contract to develop the SDB in October 2003. A focused lethality munition (FLM) warhead for the SDB I is being developed under a Joint Capability Technology Demonstration (JTCD) program, aimed at providing pinpoint strike capability with low collateral damage. The first 50 were delivered in March 2008 for operational assessment.

SDB II. Increment 2 under development in a joint interest program between a Boeing/Lockheed Martin team and Raytheon, providing a capability to attack mobile targets from standoff in all weather. One contractor will be selected following the risk reduction phase, expected to run through late 2009.

GBU-54 LJDAM

A joint USAF-Navy INS/GPS-guided weapon equipped with a laser seeker, carried by fighters and bombers, providing highly accurate, autonomous, all-weather conventional bombing capability against stationary and moving targets.

Function: Air-to-surface guided bomb.

First Flight: 2005.

Delivered: April 2008-mid 2009 (planned).

IOC: 2008.

Production: 400 laser guidance kits (planned).

Contractor: Boeing.

Guidance: INS/GPS/laser.

Dimensions: Mk 82 with JDAM 8 ft.

Weight: 552/558 lb.

Performance: range up to 17 miles.

COMMENTARY

Developed to satisfy an urgent operational requirement for an extremely accurate precision weapon capable of destroying high-speed targets in Afghanistan and Iraq, the GBU-54 combines a laser guidance kit with the GPS/INS-based navigation of existing 500-lb GBU-38 JDAMs. First combat deployment occurred August 2008 from F-16s over Iraq.

Massive Ordnance Air Blast (MOAB) Bomb

Brief: A massive precision guided munition (PGM) designed to be dropped by B-1, B-2, or B-52 bombers.

Function: Massive bomb.

Guidance: GPS/INS.

Warhead: 18,000 lb, high explosive.

Dimensions: length 30 ft, diameter 3.3 ft.

Weight: 21,500 lb.

COMMENTARY

On March 11, 2003, USAF live-tested the largest PGM developed to date. As with the earlier unguided "Daisy Cutter" bomb, the MOAB is dropped from the rear of a C-130 aircraft but does not require a parachute.

Wind-Corrected Munitions Dispenser (WCMD)

Brief: A tail kit fitted to various dispenser weapons that provides inertial guidance system corrections for launch transients and wind effects to enhance accuracy.

Function: Guidance tail kit.

First Flight: February 1996.

Delivered: from 2000.

IOC: FY00.

Production: WCMD: 27,700 (planned). WCMD-ER: 100.

Contractor: Lockheed Martin.

Dimensions: length 1.4 ft, diameter 1.3 ft.

Weight: WCMD: 100 lb. WCMD-ER: about 200 lb.

Performance: WCMD: range about eight miles. WCMD-ER: about 40 miles.

COMMENTARY

WCMD. USAF is modifying standard SUU-64/65/66 tactical munition dispensers with guidance kits to compensate for wind drift on downward flight from high altitudes. The combat-proven WCMD kits include an INS guidance unit, movable tail fins that pop out in flight, and a signal processor. The kits when fitted on CBU-87/89/97 inventory cluster weapons are designated: CEM (CBU-103), Gator (CBU-104), SFW (CBU-105), and PAW (CBU-107). Successful flight testing began in February 1996; WCMDs are now operational on A-10, B-1, B-52, F-15E, and F-16 aircraft. Objective aircraft include B-2 and F-35.

Satellite Systems

Advanced EHF (AEHF)

Brief: Joint service satellite communications system that provides global, secure, protected, and jam-resistant communications for high priority air, ground, and sea assets.

Function: Near-worldwide, secure, survivable satellite communications.

Operator: AFSPC.

First Launch: 2009 (planned).

IOC: June 2010 (planned).

Constellation: four satellites.

Design Life: 14 years.

Launch Vehicle: Atlas V; Delta IV.

Unit Location: Schriever AFB, Colo.

Orbit Altitude: 22,000+ miles (geosynchronous).

Contractor: Lockheed Martin, Northrop Grumman team

for system development and demonstration.

Dimensions: length 32 ft (across payload axis), width 75.8 ft (across solar array axis).

Weight: approx 14,500 lb at launch, 9,000 lb on orbit.

Performance: 10 times the capability of the Milstar Block II satellite.

COMMENTARY

The Advanced Extremely High Frequency (AEHF) system comprises four geosynchronous Earth orbit (GEO) satellites that will provide 10 times the capacity of the 1990s-era Milstar satellites. Advanced EHF allows the President, Secretary of Defense, and combat forces to control their tactical and strategic forces at all levels of conflict through general nuclear war and supports the attainment of information superiority. AEHF will provide connectivity across the spectrum of mission areas, including air, land, and naval warfare; special operations; strategic nuclear operations; strategic defense; theater missile defense; and space operations and intelligence.

Defense Meteorological Satellite Program

Brief: Satellites that collect air, land, sea, and space environmental data to support worldwide strategic and tactical military operations. Also shares data with civil agencies.

Function: Space and Earth environmental data collection satellite.

Operator: National Polar-orbiting Operational Environmental Satellite System (NPOESS) integrated program office.

First Launch: May 23, 1962.

IOC: 1965.

Constellation/on-orbit: two.

Design Life: 48 months.

Launch Vehicle: Delta IV and Atlas V.

Unit Location: Suitland, Md. (operations); Schriever AFB, Colo. (AFRC-manned backup operations center).

Orbit Altitude: approx 527 miles.

Contractor: Lockheed Martin; Northrop Grumman.

Power Plant: solar arrays generating 1,200-1,300 watts.

Dimensions: length 25 ft (with array deployed), width 4 ft.

Weight: 2,545 lb (including 772-lb sensor).

Performance: DMSP satellites orbit Earth in polar orbits and primary sensor scans an area 1,800 miles wide. Each system covers the Earth in about 12 hr.

COMMENTARY

For the last 40+ years, the DMSP constellation has provided high-quality, timely weather information to strategic and tactical warfighters worldwide. The operational linescan sensor "sees" visible and IR cloud-cover imagery to analyze cloud patterns. Secondary instruments include microwave imagers and sounders and a suite of space environment sensors that provide critical land, sea, and space environment data required by US forces across the globe. This data is also shared with civil agencies. The DMSP constellation will be replaced by the tri-agency NPOESS late in this decade.

Block 5D-2. The last Block 5D-2 satellite was launched in December 1999.

Block 5D-3. Two operational DMSP Block 5D-3 satellites survey the entire Earth four times a day. DMSP F16, the first Block 5D-3 satellite, was launched successfully on Oct. 18, 2003. (DMSP F15, which used a 5D-3 satellite bus but 5D-2 sensors, was launched Dec. 12, 1999 and is credited as the first 5D-3 launch.) Block 5D-3 satellites have an improved spacecraft bus and sensors that provide for longer and more capable missions. The SLEP planned for F19 and F20, and the successful flyout of the DMSP Block 5D-3 satellites, will help ensure a seamless transition to the NPOESS program.

Defense Satellite Communications System

Brief: A spacecraft traveling in geosynchronous orbit used to transmit SHF high-priority C2 communication.

Function: Communications satellite.

Operator: AFSPC.

First Launch: 1971 (DSCS II); 1982 (DSCS III); 2000 (DSCS III/SLEP).

IOC: Dec. 13, 1978 (DSCS II).

Constellation: five (III).

Design Life: 10 yr (III).

Launch Vehicle: Atlas II.

Unit Location: Schriever AFB, Colo.

Orbit Altitude: 22,000+ miles in geosynchronous orbit.

Contractor: Lockheed Martin.

Power Plant: solar arrays generating 1,269 watts, decreasing to 980 watts after 10 yr; 1,500 watts (SLEP).

Dimensions: rectangular body 6 x 6 x 7 ft; 38-ft span with solar arrays deployed.

Weight: 2,580 lb; 2,716 lb (SLEP).

Performance: DSCS satellites orbit Earth at about 22,000 miles altitude and employ six SHF transponder channels for secure voice and high-rate data communications.

COMMENTARY

DSCS III satellites support globally distributed DOD and national security users. The final four of 14 satellites



GBU-39 Small Diameter Bombs (USAF photo)

received SLEP modifications, providing substantial capacity improvements through higher power amplifiers, more sensitive receivers, and additional antenna connectivity options. The DSCS communications payload includes six independent superhigh frequency (SHF) transponder channels that cover a 500 MHz bandwidth. Three receive and five transmit antennas provide selectable options for Earth coverage, area coverage, and/or spot beam coverage. A special-purpose single channel transponder is also on board.

The DSCS III system provides the capabilities needed for effective implementation of worldwide military communications. It can adapt to dynamic operating conditions and perform under stressed environments, providing nuclear hardened, anti-jam, high data rate, long-haul communications to military users globally. The final DSCS III satellite was launched in August 2003. The modernization of satellite communications will continue as the Wideband Global SATCOM (WGS) is deployed.

Defense Support Program

Brief: An early warning spacecraft that travels in geosynchronous orbit and provides alert of possible ballistic missile attack on US forces or homeland.

Function: Strategic and tactical launch detection system.
Operator: AFSPC.

First Launch: November 1970.

IOC: circa 1972.

Constellation: classified.

Design Life: three yr requirement and five yr goal.

Launch Vehicle: Titan IV with inertial upper stage; Delta IV Heavy EELV.

Unit Location: Buckley AFB, Colo.

Orbit Altitude: 22,000+ miles in geosynchronous orbit.

Contractor: TRW (now Northrop Grumman); Aerojet.

Power Plant: solar arrays generating 1,485 watts.

Dimensions: diameter 22 ft, height 32.8 ft, with solar paddles deployed.

Weight: 5,000 lb (approx).

Performance: orbits at approx 22,000 miles altitude in geosynchronous orbit; uses IR sensors to sense heat from missile and booster plumes against Earth's background.

COMMENTARY

The incredibly flexible Defense Support Program (DSP) satellite system was used extensively in Desert Storm to detect theater missile launches against coalition forces. Though not designed to spot and track smaller missiles, the system was highly successful in detecting launches, enabling timely warnings of Iraqi Scud attacks. The Space Based Infrared System (SBIRS) mission control station (MCS), located at Buckley AFB, Colo., became operational in December 2001 and now performs both the strategic and theater missile warning missions.

DSP satellites are a key part of the North American and theater early warning systems, capable of detecting missile launches and nuclear detonations. Warning data are fed to NORAD and US Strategic Command early warning centers at Cheyenne Mountain AFS, Colo. Since the first launch, DSP satellites have provided an uninterrupted early warning capability to the US. The 23rd and final DSP launched in November 2007. America's early warning capability will be modernized with the introduction of the new SBIRS to be phased in at a future date.

Global Positioning System

Brief: A space-based radio-positioning system that provides 24-hour worldwide highly accurate three-dimensional location information and precision velocity and timing services to military and civilian users.

Function: Worldwide navigation satellite constellation.
Operator: AFSPC.

First Launch: Feb. 22, 1978.

IOC: Dec. 9, 1993.

Constellation: Nominal 24 satellites in six orbital planes; max 30 sats; 28 operational (as of Jan. 2, 2009).

Design Life: 7.5 yr (II/IIA); 10 yr (IIR/IIR-M); 12 yr (IIF).

Launch Vehicle: Delta II, Delta IV, Atlas V.

Unit Location: Schriever AFB, Colo.

Orbit Altitude: 10,988 miles.
Contractor: Boeing (II, IIA, IIF); Lockheed Martin (IIR, IIR-M).

Power Plant: solar panels generating 700 watts (II/IIA); 1,136 watts (IIR/IIR-M); up to 2,900 watts (IIF).

Dimensions: IIR/IIR-M: 5 x 6.3 x 6.25 ft, span incl solar panels 38 ft; IIF: 9.6 ft x 6.5 ft x 12.9 ft (span incl solar panels 43.1 ft).

Weight: on orbit: 2,370 lb (IIR/IIR-M); 3,439 lb (IIF).

Performance: GPS satellites orbit the Earth every 12 hr, emitting continuous navigation signals. The signals are so accurate that time can be figured to within one-millionth of a second, velocity within a fraction of a mile per hr, and location to within a few ft. Receivers are used in aircraft, ships, and land vehicles and can also be handheld.

COMMENTARY

Worldwide military operations, such as precision bombing, CSAR, mapping, and rendezvous, are successful in part due to the 24-hour, worldwide position navigation

and timing service provided by the Global Positioning System (GPS) navigation satellite constellation. Accurate three-dimensional (latitude, longitude, and altitude) position, velocity, and precise time are provided continuously in real time to support an unlimited number of users around the globe, both civilian and military. Concern over potential enemy denial of GPS is being addressed under GPS modernization efforts. The modified Block IIR-M satellites, launched beginning September 2005, offers a variety of enhanced features for the GPS user, such as two new signals, enhanced encryption and anti-jamming capabilities for the military user, as well as a second civil signal. Block IIF satellites will have an extended design life, faster processors, and a new civil signal on a third frequency. Launch is scheduled for late 2009. Future generation GPS III satellites, with advanced anti-jam and higher quality data, are slated for launch 2014.

Milstar Satellite Communications System

Brief: A joint service satellite communications system that provides global, secure, protected, and jam-resistant strategic and tactical communications at all levels of conflict for high-priority air, ground, and sea assets.

Function: Communications satellite.

Operator: AFSPC.

First Launch: Feb. 7, 1994.

IOC: July 1997 (Milstar I).

Constellation: five.

Design Life: 10 yr.

Launch Vehicle: Titan IV/Centaur.

Unit Location: Schriever AFB, Colo.

Orbit Altitude: 22,300 miles.

Contractor: Lockheed Martin; Boeing; TRW (now Northrop Grumman).

Power Plant: solar arrays generating 8,000 watts.

Dimensions: length 51 ft, width 116 ft with full solar array extension.

Weight: 10,000 lb.

Performance: constellation consists of five satellites in low-inclined geosynchronous orbit, providing worldwide coverage between 65° north and 65° south latitude. The oldest two satellites are still working beyond their 10-yr design life.

COMMENTARY

The backbone of strategic-tactical communications, Milstar is a joint service communications system that provides secure, jam-resistant worldwide communications through crosslinked satellites, eliminating the need for ground relay stations. Worldwide operations are made possible by this 24-hour, all-weather capability, ready to support any deployment at a moment's notice. The Milstar inventory was fully deployed in 2003, and modernization of satellite communications will continue with the Advanced EHF (AEHF) constellation deployment.

Space Based Infrared System High

Brief: Advanced surveillance system for missile warning, missile defense, battlespace characterization, and technical intelligence. System includes satellites in geosynchronous Earth orbit (GEO) and highly elliptical orbit (HEO).

Function: IR space surveillance.

Operator: AFSPC.

First Launch: (planned) GEO: Fiscal 2010.

IOC: TBD.

Constellation: four GEO sats, two HEO sensors.

Design Life: not available.

Launch Vehicle: GEO: Atlas V.

Unit Location: Buckley AFB, Colo.

Orbit Altitude: High at approx 22,300 miles.

Contractor: Lockheed Martin; Northrop Grumman.

Power Plant: solar array, 2,435 watts.

Dimensions: 6 x 7 x 17 ft.

Weight: 5,442 lb.

COMMENTARY

The follow-on to the DSP is the Space Based Infrared System (SBIRS). The system includes GEO satellites, HEO payloads, and ground assets.

SBIRS is being fielded incrementally. Increment 1 consolidated all DSP ground processing in one CONUS master control station at Buckley AFB, Colo. IOC was declared Dec. 18, 2001. Increment 2 will field the space and ground assets. SBIRS is in the EMD phase led by a Lockheed Martin team. Following initial early on-orbit checkout, HEO-1, the first SBIRS payload, was cleared for operational service late 2008. HEO-2 is expected to follow early 2009. The payloads operating in HEO are the first components of the Increment 2 constellation.

Space Based Surveillance System (SBSS)

Brief: Planned replacement for the Midcourse Space Experiment/Space Based Visible (MSX/SBV) satellite that undertakes tracking and optical signature collection of Earth-orbiting objects.

Function: Space surveillance.

Operator: AFSPC.

First Launch: 2009 (planned).

IOC: TBD.



Milstar (Lockheed Martin photo)

Constellation: none.

Design Life: not available.

Launch Vehicle: Minotaur IV.

Unit Location: not available.

Orbit Altitude: 528 miles.

Contractor: Northrop Grumman; Boeing subcontractor for Pathfinder satellite.

Power Plant: not available.

Dimensions: not available.

Weight: not available.

COMMENTARY

SBSS is a planned follow-on to the experimental MSX/SBV satellite and will track and collect optical signatures of Earth-orbiting objects. One Pathfinder satellite is due to be launched in spring 2009 and four operational satellites are planned for around 2014.

Wideband Global SATCOM (WGS)

Brief: Satellites that provide high-capacity communications for deployed forces (air, land, and sea).

Function: Communications satellite.

Operator: AFSPC.

First Launch: October 2007.

IOC: TBD.

Constellation: six satellites.

Design Life: 14 years.

Launch Vehicle: Atlas V, Delta IV.

Unit Location: Schriever AFB, Colo.

Orbit Altitude: GEO.

Contractor: Boeing.

Power Plant: solar arrays generating 9,934 watts.

Dimensions: based on Boeing 702 Bus.

Weight: 13,000 lb at launch.

Performance: approx 12 times the capability of a DSCS satellite.

COMMENTARY

Wideband Global SATCOM, previously known as the Wideband Gap-filler System, is designed to augment DSCS III and the Navy's Global Broadcast System (GBS) Phase II. WGS is a fully duplexed communications platform offering warfighters a significant increase in capacity, connectivity, and interoperability. It provides two-way services for national leaders, Diplomatic Telecommunications Service, Defense Information System Network, and all military ground fixed and mobile users. In addition, it will provide direct broadcast of digital multimedia, high-bandwidth imagery, and video information directly from global and theater sites to deployed warfighters. Primarily a commercial product, the satellites feature X-band (DSCS III-like), Ka-band broadcast (GBS Phase 2-like), two-way Ka-band services, and cross-channelization between its X- and Ka-band services. Full operational capability (FOC) is expected 2012 with launch of the fifth satellite. ■

